

PRODUCT-DETAILS

3GKP224210-ADK

Flameproof IE3 Premium Efficiency LV Motors, 18,5 kW, 400 V (3GKP224210-ADK)



General Information

Product ID	3GKP224210-ADK
ABB Type Designation	M3KP 225SMA 8
Catalog Description	Flameproof IE3 Premium Efficiency LV Motors, 18,5 kW, 400 V (3GKP224210-ADK)

Additional Information

ABB Type Designation	M3KP 225SMA 8
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6313/C3
Bearing NDE	6312/C3
Connection Configuration	D
Country of Origin	Finland (FI)
Customs Tariff Number	85015230
Direction of Rotation	Both sides
Electrical Data	

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T4	50 Hz	690 V	18.50 kW	736 r/min	23.00 A	0.740	90.10 %	240.00 N-m	5.20
D	T4	50 Hz	400 V	18.50 kW	736 r/min	39.80 A	0.740	90.10 %	240.00 N-m	5.20
Y	T4	50 Hz	660 V	18.50 kW	735 r/min	23.80 A	0.750	90.10 %	240.00 N-m	4.70
D	T4	50 Hz	380 V	18.50 kW	735 r/min	41.20 A	0.750	90.10 %	240.00 N-m	4.70
D	T4	50 Hz	415 V	18.50 kW	737 r/min	39.20 A	0.720	90.10 %	240.00 N-m	5.60
D	T4	60 Hz	460 V	18.50 kW	890 r/min	35.10 A	0.720	90.20 %	198.00 N-m	5.90

EX-Protection	Exdbeb
Frame Material	Cast Iron
Frame Size	225
Frequency (f)	50 Hz
Gas Group	IIB
Gross Weight	432 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE3 Full Load (100%) 90.1 % Partial Load (75%) 90.4 % Partial Load (50%) 89.6 %
IE Class Data (60 Hz)	IE Class IE3 Full Load (100%) 90.2 % Partial Load (75%) 90.3 % Partial Load (50%) 89.0 %
IM Class	IMB3 IM1001
Input Voltage (U _{in})	400 V
Insulation Class	ICLF
IP Class	IP55
Made To Order	No
Medium Description	18.5kW, 8 Poles, Frame Size 225, 3 Phases, 400V, 50Hz, IP55 Enclosure, IMB3/IM1001 Mounting (3GKP224210-ADK)
Minimum Order Quantity	1 piece
Number of Poles (High)	8
Order Multiple	1 piece
Output Power	18,5 kW
Package Level 1 Units	0 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Depth / Length	901 mm
Product Net Height	620 mm
Product Net Weight	422 kg
Product Net Width	432 mm
Product Type	3KP3_M3KP_IE3_Flameproof_Exde_motor
Quote Only	No
Selling Unit of Measure	piece
Short Description	18.5kW, 8P, Frame Size 225, 3PH, 400V, 50Hz, IP55, IMB3/IM1001
Temperature Class Default	T4
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
UNSPSC	26101100
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Flameproof Motors → Flameproof IE3 Premium Efficiency LV Motors

