


PRODUCT-DETAILS

3GKP312230-ADG

M3KP 315SMC 4



General Information

Product ID	3GKP312230-ADG
ABB Type Designation	M3KP 315SMC 4
Catalog Description	M3KP 315SMC 4

Additional Information

ABB Type Designation	M3KP 315SMC 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6319/C3
Bearing NDE	6316/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015381
Direction of Rotation	Both sides
EX-Protection	Exde

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Factor	Efficiency	Torque	IS/IN
Y	T4	50 Hz	690 V	160.00 kW	1487 r/min	169.00 A	0.850	95.30 %	1027.00 N·m	7.20
D	T4	50 Hz	400 V	160.00 kW	1487 r/min	284.00 A	0.850	95.30 %	1027.00 N·m	7.20
D	T4	50 Hz	415 V	160.00 kW	1488 r/min	277.00 A	0.840	95.40 %	1027.00 N·m	7.80

Gas Group	IIB
Gross Weight	1040 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE2 Full Load (100%) 95.3 % Partial Load (75%) 95.3 % Partial Load (50%) 94.8 %
IM Class	IMB3 IM1001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3KP 315SMC 4
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Output Power	160 kW
Package Level 1 Units	1 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	1020 kg
Product Type	3KP2__M3KP_IE2_Flameproof_Exde_motor
Quote Only	No
Selling Unit of Measure	piece
Sound dB (A)	70 dB(A)
Temperature Class Default	T4
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)

Categories

Motors and Generators → Motors and Generators for Explosive Atmospheres → Flameproof Motors → Flameproof IE2 High Efficiency LV Motors

