



PRODUCT-DETAILS

3GKP401810-BDG

M3KP 400LKA 2

General Information

Product ID	3GKP401810-BDG
ABB Type Designation	M3KP 400LKA 2
Catalog Description	M3KP 400LKA 2

Additional Information

ABB Type Designation	M3KP 400LKA 2
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6317M/C3
Bearing NDE	6317M/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015394
EX-Protection	Exde

Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Efficiency Factor	Torque	IS/IN
Y	T4	50 Hz	690 V	560.00 kW	2988 r/min	541.00 A	0.890 97.20 %	1789.00 N·m	7.80
D	T4	50 Hz	400 V	560.00 kW	2988 r/min	934.00 A	0.890 97.20 %	1789.00 N·m	7.80
D	T4	50 Hz	415 V	560.00 kW	2989 r/min	919.00 A	0.880 97.20 %	1789.00 N·m	8.40

Gas Group	IIB
Gross Weight	3110 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE4 Full Load (100%) 97.2 % Partial Load (75%) 97.1 % Partial Load (50%) 96.5 %
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3KP 400LKA 2
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	2
Order Multiple	1 piece
Package Level 1 Units	1 pallet (lift)

Product Name	3-Phase squirrel cage motor
Product Net Weight	3070 kg
Product Type	3KP2__M3KP_IE2_Flameproof_Exde_motor
Quote Only	No
Selling Unit of Measure	piece
Temperature Class Default	T4
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)