



PRODUCT-DETAILS

# 3GKP452510-BDG

## M3KP 450LA 4

### General Information

Product ID	3GKP452510-BDG
ABB Type Designation	M3KP 450LA 4
Catalog Description	M3KP 450LA 4

### Additional Information

ABB Type Designation	M3KP 450LA 4
Altitude	1000 m
Ambient Temperature	40 °C
Bearing	6326/C3
Bearing NDE	6322/C3
Country of Origin	Finland (FI)
Customs Tariff Number	85015399
EX-Protection	Exde

#### Electrical Data

Conn	Temp Class	Freq	Voltage	Power	Speed	Current	Power Efficiency Factor	Torque	IS/IN
D	T4	50 Hz	415 V	780.00 kW	1492 r/min	1335.00 A	0.840 96.70 %	4992.00 N·m	7.60
D	T4	50 Hz	400 V	780.00 kW	1491 r/min	1369.00 A	0.850 96.70 %	4995.00 N·m	7.10

Gas Group	IIB
Gross Weight	4090 kg
IC Class	IC411
IE Class Data (50 Hz)	IE Class IE4 Full Load (100%) 96.7 % Partial Load (75%) 96.6 % Partial Load (50%) 95.9 %
IM Class	IMB5 IM3001
IP Class	IP55
Insulation Class	ICLF
Invoice Description	M3KP 450LA 4
Made To Order	No
Minimum Order Quantity	1 piece
Number of Poles (High)	4
Package Level 1 Units	1 pallet (lift)
Product Name	3-Phase squirrel cage motor
Product Net Weight	4050 kg
Product Type	3KP2__M3KP_IE2_Flameproof_Exde_motor

Quote Only	No
Selling Unit of Measure	piece
Temperature Class Default	T4
Terminator Box Location	Top
Two Speed Motor	No
Type of Duty	S1
Voltage Code	D
WEEE Category	4. Large Equipment (Any External Dimension More Than 50 cm)