

PRODUCT-DETAILS

FP A 2 63/300 FP A 2 63/300 Residual Current Circuit Breaker 2P A type 300 mA



General Information

Extended Product Type	FP A 2 63/300
Product ID	4TQA603345R0000
EAN	5411815226328
Catalog Description	FP A 2 63/300 Residual Current Circuit Breaker 2P A type 300 mA
Long Description	The FP series RCCB is providing the protection for the people against the leakage currents. Including different types and sensitivities for a wide set of applications.

Technical	
Standards	IEC/EN 60898-1
Type of Residual Current	A type
Rated Operational Voltage	240 V AC
Rated Insulation Voltage (Ui)	acc. to IEC/EN 60664-1 440 V
Rated Impulse Withstand Voltage (U _{imp})	6 kV
Input Voltage Type	AC
Rated Current (I _n)	63 A
Rated Residual Current	300 mA
Rated Service Short-	10 kA

© 2024 ABB. All rights reserved.

Subject to change without notice

Circuit Breaking	
Capacity (I _{cs})	
Maximum Surge Current	250 kA
Rated Frequency (f)	50/60 Hz
Number of Protected Poles	2
Number of Poles	2
Operating Characteristic	Instantaneous
Position of Neutral Terminals	Right
Mounting Type	DIN-Rail
Accessories Available	Yes
Rated Cross-Section	1 - Solid-Core 1 1 mm² 4 - Multi-Wired 1 1 mm²

Environmental	
Ambient Air	Operation 40 40 °C
Temperature	
Degree of Protection	IP2C
Pollution Degree	3
RoHS Status	Following EU Directive 2011/65/EU
RoHS Information	2CSC423016D2701
Conflict Minerals	9AKK108468A3363
Reporting Template	
(CMRT)	

Technical UL/CSA	
Short-Circuit Current	0.0003 A
Rating (SCCR)	

Dimensions	
Width in Number of Modular Spacings	2
Product Net Width	36 mm
Product Net Height	70 mm
Product Net Depth / Length	91 mm
Product Net Weight	0.197 kg
Built-In Depth (t ₂)	44 mm

Ordering	
Package Level 1 Units	box 1 piece
Package Level 1 Gross Weight	0.213 kg

Certificates and Declarations

Declaration of	No declaration needed
Conformity - CE	

In structions and	Ki - Januari - Angelandari
Instructions and Manuals	No document needed
Popular Downloads	
Data Sheet, Technical Information	No document needed
Classifications	
	EC000003 - Residual current circuit breaker (RCCB)
Classifications ETIM 8 ETIM 9	EC000003 - Residual current circuit breaker (RCCB) EC000003 - Residual current circuit breaker (RCCB)
ETIM 8	
ETIM 8 ETIM 9 WEEE Category	EC000003 - Residual current circuit breaker (RCCB)
ETIM 8 ETIM 9	EC000003 - Residual current circuit breaker (RCCB) 5. Small Equipment (No External Dimension More Than 50 cm) Business To Business
ETIM 8 ETIM 9 WEEE Category WEEE B2C / B2B CN8	EC000003 - Residual current circuit breaker (RCCB) 5. Small Equipment (No External Dimension More Than 50 cm)
ETIM 8 ETIM 9 WEEE Category WEEE B2C / B2B	EC000003 - Residual current circuit breaker (RCCB) 5. Small Equipment (No External Dimension More Than 50 cm) Business To Business 8536 20 10

Categories

Low Voltage Products and Systems \rightarrow Modular DIN Rail Products \rightarrow AEG \rightarrow Residual Current Devices RCDs



© 2024 ABB. All rights reserved.

2024/01/17

