


PRODUCT-DETAILS

BA-G 3/12/10

BA-G 3/12/10 Busbar



General Information

Extended Product Type	BA-G 3/12/10
Product ID	4TQA650184R1012
EAN	5413656501848
Catalog Description	BA-G 3/12/10 Busbar
Long Description	BA-G 3/12/10 Fork busbar, 3 Phases, 12 PINs, 10 mm ²

Technical

Rated Operational Voltage	500 V Maximum 500 V
Voltage Protection Level (Up)	4
Rated Conditional Short-Circuit Current (I_{nc})	25 kA
Rated Uninterrupted Current (I_u)	125 A
Pitch	18.0
Number of Poles	3
Number of Phases	3
Number of Mountable Devices	4
Connection Type	Fork
Rated Cross-Section	10 mm ²

Environmental

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Information	9AKK107680A9762
REACH Declaration	No declaration needed
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363

Dimensions

Width in Number of Modular Spacings	12
Product Net Width	210 mm
Product Net Height	11 mm
Product Net Depth / Length	210 mm
Product Net Weight	0.026 kg

Ordering

Package Level 1 Units	carton 1 piece
Package Level 1 Gross Weight	0.896 kg

Certificates and Declarations

Declaration of Conformity - CE	9AKK107680A9762
--------------------------------	-----------------

Installation

Instructions and Manuals	No document needed
--------------------------	--------------------

Popular Downloads

Data Sheet, Technical Information	No document needed
-----------------------------------	--------------------

Classifications

ETIM 8	EC000215 - Phase busbar
ETIM 9	EC000215 - Phase busbar
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	8536 90 01
UNSPSC	39121117
eClass	V11.0 : 27371306
IDEA Granular Category Code (IGCC)	4378 >> Phase busbar
Object Classification Code	Q

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → AEG → Busbars and Accessories

