


PRODUCT-DETAILS

BA-G 2/12/10 BA-G 2/12/10 Busbar



Extended Product Type	BA-G 2/12/10
Product ID	4TQA650229R1012
EAN	5413656502296
Catalog Description	BA-G 2/12/10 Busbar
Long Description	BA-G 2/12/10 Fork busbar, 2 Phases, 12 PINs, 10 mm2

Technical	
Rated Operational Voltage	500 V Maximum 500 V
Voltage Protection Level (Up)	4
Rated Conditional Short- Circuit Current (I _{nc})	25 kA
Rated Uninterrupted Current (I _u)	125 A
Pitch	18.0
Number of Poles	2
Number of Phases	2
Number of Mountable Devices	6
Connection Type	Fork
Color	light grey

BA-G 2/12/10 2

Rated Cross-Section	10 mm²	
Environmental		
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019	
RoHS Information	9AKK107680A9762	
REACH Declaration	No declaration needed	
Conflict Minerals	9AKK108468A3363	
Reporting Template (CMRT)		
Dimensions		
Width in Number of Modular Spacings	12	
Product Net Width	210 mm	
Product Net Height	8 mm	
Product Net Depth / Length	210 mm	
Product Net Weight	0.026 kg	
Ordering		
Package Level 1 Units	carton 1 piece	
Package Level 1 Gross	0.706 kg	
Weight	0.700 kg	
Certificates and Declarations		
Declaration of Conformity - CE	9AKK107680A9762	
Installation		
Instructions and Manuals	No document needed	
Popular Downloads Data Sheet, Technical	No document needed	
Information	No document needed	
Classifications		
ETIM 8	EC000215 - Phase busbar	
ETIM 9	EC000215 - Phase busbar	
WEEE Category	Small Equipment (No External Dimension More Than 50 cm)	
WEEE B2C / B2B	Business To Business	
CN8	8536 90 01	
UNSPSC	39121117	
eClass	V11.0 : 27371306	
IDEA Granular Category Code (IGCC)	4378 >> Phase busbar	
Object Classification Code	Q	

BA-G 2/12/10 3

Categories

Low Voltage Products and Systems \rightarrow Modular DIN Rail Products \rightarrow AEG \rightarrow Busbars and Accessories

