

PRODUCT-DETAILS

BA-SU 2/112/10 BA-SU 2/112/10 Busbar

General Information	
Extended Product Type	BA-SU 2/112/10
Product ID	4TQA650381R1055
EAN	5413656503811
Catalog Description	BA-SU 2/112/10 Busbar
Long Description	BA-SU 2/110/10 Busbar for S200C, 2 Phases, 110 PINs, 10 mm2

Technical	
Rated Operational Voltage	500 V Maximum 500 V
Voltage Protection Level (Up)	4
Rated Conditional Short- Circuit Current (I _{nc})	25 kA
Rated Uninterrupted Current (I _u)	63 A
Pitch	9.0
Number of Poles	2
Number of Phases	2
Number of Mountable Devices	56
Connection Type	Pin
Rated Cross-Section	10 mm²

© 2024 ABB. All rights reserved.

2024/01/17

Subject to change without notice

Environmental	
RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Information	9AKK107680A9762
REACH Declaration	No declaration needed
Conflict Minerals Reporting Template (CMRT)	9AKK108468A3363
Dimensions	
Width in Number of Modular Spacings	56
Product Net Width	1016 mm
Product Net Height	15 mm
Product Net Depth / Length	1000 mm
Product Net Weight	0.241 kg
Ordering	
Package Level 1 Units	carton 1 piece
Package Level 1 Gross Weight	6.961 kg
Certificates and Declarations	
Declaration of Conformity - CE	9AKK107680A9762
Installation	
Instructions and Manuals	No document needed
Popular Downloads	
Data Sheet, Technical Information	No document needed
Classifications	
ETIM 8	EC000215 - Phase busba EC000215 - Phase busba
ETIM 9 WEEE Category	EC000215 - Phase busbar 5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	5. Small Equipment (No External Dimension More Than 50 Cm) Business To Business
CN8	8536 90 01
UNSPSC	39121117
eClass	V11.0 : 27371306
IDEA Granular Category Code (IGCC)	4378 >> Phase busba

Categories

Low Voltage Products and Systems \rightarrow Modular DIN Rail Products \rightarrow AEG \rightarrow Busbars and Accessories

