

PRODUCT-DETAILS

# E880+252D80

## E880+252D80 High Performance MCB

### Información General

Tipo de producto extendido	E880+252D80
Código de producto	2CCG000304R0001
EAN	5413656649229
Descripción corta	E880+252D80 High Performance MCB
Descripción larga	E880+251C100 High Performance MCB, 25 kA, 2 Pole, D characteristic, 80 A

### Technical

Standards	IEC/EN 60947-2 IEC/EN 60898-1
Tripping Characteristic	D
Rated Voltage ( $U_r$ )	254/440 V AC 250 V DC
Rated Operational Voltage	254/440 V AC 250 V DC
Operational Voltage	Maximum 230/400 V AC Minimum 12 V AC
Rated Insulation Voltage ( $U_i$ )	acc. to IEC/EN 60664-1 500 V AC
Rated Impulse Withstand Voltage ( $U_{imp}$ )	8 kV
Rated Current ( $I_n$ )	80 A
Rated Operational Current ( $I_e$ )	80 A
Rated Short-Circuit Capacity ( $I_{cn}$ )	(230 / 400 V AC) 15 kA
Rated Ultimate Short-Circuit Breaking Capacity ( $I_{cu}$ )	(240 / 415 V AC) 25 kA (254 / 440 V AC) 15 kA (250 V DC) 10 kA
Rated Service Short-Circuit Breaking Capacity ( $I_{cs}$ )	(240 / 415 V AC) 18 kA (254 / 440 V AC) 10 kA (250 V DC) 10 kA
Frequency (f)	50 / 60 Hz
Rated Frequency (f)	50 ... 60 Hz
Power Loss	12.8 W at Rated Operating Conditions per Pole 6.4 W
Contact Position Indication	ON / OFF / TRIP
Energy Limiting Class	3 4000 cycle
Number of Poles	2

Overvoltage Category	IV
Tightening Torque	3.5 N-m
Actuator Marking	I / O
Housing Material	Insulation group I, RAL 7035
Mounting on DIN Rail	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
Mounting Position	any
Recommended Screw Driver	Pozidriv 2
Remarks	Connection from top and bottom Connecting with CU only IP40 in enclosure with cover Cage terminal with captille screw
Number of Batteries	0
Connecting Capacity	Flexible 1 ... 50 mm <sup>2</sup> Stranded 1 ... 70 mm <sup>2</sup>
Terminal Type	Screw Terminals

## Ambiente

Reference Ambient Air Temperature	acc. to IEC60947-2 30 °C acc. to EN60898-1 30 °C
Grado de protección	IP20
Pollution Degree	3
Resistance to Vibrations acc. to IEC 60068-2-6	2 - 13.2 Hz / 1mm 13.2 - 100Hz / 0.7g with load 100% x 1e
Resistance to Shock acc. to IEC 60068-2-27	5 g 30 ms

## Dimensiones

Ancho del product	54 mm
Alto del producto	95 mm
Largo del product	82.5 mm
Peso del product	490 g

## Información de Embalaje

Embalaje Nivel 1 Unidades	box 1 piece
Embalaje Nivel 1 Ancho	105 mm
Embalaje Nivel 1 Alto	99 mm
Embalaje Nivel 1 Largo	60 mm
Embalaje Nivel 1 Peso	510 g
Embalaje Nivel 1 EAN	5413656649229

## Clasificación

Cantidad mínima de pedido	1 piece
Código arancelario	85362090
Country of Origin	Switzerland (CH)

## Certificados y Declaraciones (Número de Documento)

Declaración de conformidad - CE	No declaration needed
Instrucciones y manuales	No document needed

---

## Descargas Populares

---

Ficha técnica, información técnica	No document needed
Instrucciones y manuales	No document needed

---

---

## Clasificaciones

---

ETIM 7	EC000042 - Miniature circuit breaker (MCB)
ETIM 8	EC000042 - Miniature circuit breaker (MCB)
Categoría RAEE	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	85362020
Object Classification Code	F

---

---

## Categorías

---

Productos y sistemas de baja tensión → Aparatos modulares de instalación → AEG → MCB AEG