



PRODUCT-DETAILS

E880+164D125

E880+164D125 High Performance MCB

Información General

Tipo de producto extendido	E880+164D125
Código de producto	2CCG000309R0001
EAN	5413656649267
Descripción corta	E880+164D125 High Performance MCB
Descripción larga	E880+251C100 High Performance MCB, 16 kA, 4 Pole, D characteristic, 125 A

Technical

Standards	IEC/EN 60947-2
Tripping Characteristic	D
Rated Voltage (U_r)	230/400 V AC
Rated Operational Voltage	230/400 V AC
Rated Insulation Voltage (U_i)	acc. to IEC/EN 60664-1 500 V AC
Rated Impulse Withstand Voltage (U_{imp})	6 kV
Rated Current (I_n)	125 A
Rated Operational Current (I_e)	125 A
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu})	(240 / 415 V AC) 16 kA (300 V DC) 10 kA
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(230 / 400 V AC) 10 kA
Frequency (f)	50 / 60 Hz
Rated Frequency (f)	50 ... 60 Hz
Power Loss	43.75 W at Rated Operating Conditions per Pole 10.94 W
Contact Position Indication	ON / OFF / TRIP
Energy Limiting Class	3
Number of Poles	4
Overvoltage Category	III
Tightening Torque	3.5 N·m
Actuator Marking	I / O
Housing Material	Insulation group I, RAL 7035
Mounting on DIN Rail	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715

Mounting Position	any
Recommended Screw Driver	Pozidriv 2
Remarks	Connection from top and bottom Connecting with CU only IP40 in enclosure with cover Cage terminal with captille screw
Number of Batteries	0
Connecting Capacity	Flexible 1 ... 50 mm ² Stranded 1 ... 70 mm ²
Terminal Type	Screw Terminals

Ambiente

Reference Ambient Air Temperature	acc. to IEC60947-2 30 °C acc. to EN60898-1 30 °C
Grado de protección	IP20
Pollution Degree	3

Dimensiones

Ancho del product	106 mm
Alto del producto	95 mm
Largo del product	82.5 mm
Peso del product	980 g

Información de Embalaje

Embalaje Nivel 1 Unidades	box 1 piece
Embalaje Nivel 1 Ancho	105 mm
Embalaje Nivel 1 Alto	99 mm
Embalaje Nivel 1 Largo	111 mm
Embalaje Nivel 1 Peso	1010 g
Embalaje Nivel 1 EAN	5413656649267

Clasificación

Cantidad mínima de pedido	1 piece
Código arancelario	85362090
Country of Origin	Switzerland (CH)

Certificados y Declaraciones (Número de Documento)

Declaración de conformidad - CE	No declaration needed
Instrucciones y manuales	No document needed

Descargas Populares

Ficha técnica, información técnica	No document needed
Instrucciones y manuales	No document needed

Clasificaciones

ETIM 7	EC000042 - Miniature circuit breaker (MCB)
ETIM 8	EC000042 - Miniature circuit breaker (MCB)
Categoría RAEE	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	85362020
Object Classification Code	F

Categorías

Productos y sistemas de baja tensión → Aparatos modulares de instalación → AEG → MCB AEG