

BEL-TEMANA

AnaLink temperature transmitter with built-in Pt 1000 sensor

Temperature range: -30°C to +60°C (-22° to +140°F)

Uses only 1 channel

Channel coding by BGP-COD-BAT

Easily mountable

Supplied by smart-house



GENERAL SPECIFICATIONS

| | |
|------------------------------|--------------------------------|
| Channal programming | By BGP-COD-BAT |
| Channal assignment | 1 channel, freely programmable |
| Environment | |
| Degree of protection | IP 20 |
| Operating temperature | -30° to +60°C (-22° to +140°F) |
| Storage temperature | -55° to +85°C (-67° to +185°F) |
| Mechanical resistance | |
| Shock | 15 G (11 ms) |
| Vibration | 2 G (6 to 55 Hz) |

| | | |
|------------------------|-----------------|-----------|
| Connection | Screw terminal | |
| | Pin 1: D+ | Pin 2: D- |
| Housing | | |
| Material | Housing | ABS |
| | Plug | Nylon |
| Colour | Off-white | |
| Dimensions (H x W x D) | 84 x 84 x 34 mm | |

SUPPLY SPECIFICATIONS

| | |
|---------------------------|-------------------------|
| Power supply | Supplied by smart-house |
| Rated operational current | typ. 800 µA |

TYPE SELECTION

| | |
|---------------------|----------------|
| Supply | By smart-house |
| Ordering no. | BEL-TEMANA |

DIMENSIONS

