

Data Sheet

Pressure transmitters Type **MBS 3200** and **MBS 3250**

For heavy duty applications



The compact high temperature pressure transmitter MBS 3200 is designed for use in hydraulic and almost all industrial applications, and offers a reliable pressure measurement, even under harsh environmental conditions.

MBS 3250 with integrated pulse-snubber is designed for use in hydraulic applications with severe medium influences like cavitation, liquid hammer or pressure peaks and offers a reliable pressure measurement, even under harsh environmental conditions.

The flexible pressure transmitter programme covers different output signals, absolute or gauge (relative) versions, measuring ranges from 0 – 1 to 0 – 600 bar and a wide range of pressure and electrical connections.


A robust design, an excellent vibration stability and a high degree of EMC / EMI protection equip the pressure transmitter to meet the most stringent industrial requirements.

Features

- Designed for use in harsh industrial and hydraulic environments
- For media and ambient temperatures up to 125 °C
- With integrated pulse-snubber. Protected against cavitation, liquid hammering and pressure peaks (MBS 3250)
- All standard output signals: 4 – 20 mA, 0 – 5 V, 1 – 5 V, 1 – 6 V, 0 – 10 V, 1 – 10 V and ratiometric output signal: 10-90% of supply voltage
- Enclosure and wetted parts of AISI 316L
- A wide range of pressure and electrical connections
- Fully digitally compensated
- For use in Zone 2 explosive atmospheres
- UL approved

Applications

Applications (MBS 3250)



1 Pulse-snubber

Cavitation, liquid hammer and pressure peaks may occur in hydraulic systems with changes in flow velocity, e.g. fast closing of a valve or pump starts and stops.

The problem may occur on the inlet and outlet side, even at rather low operating pressures.

Media conditions (MBS 3250)

Clogging of the nozzle may occur in liquids containing particles. Mounting the transmitter in an upright position minimizes the risk of clogging, because the flow in the nozzle is limited to the start-up period until the dead volume behind the nozzle orifice is filled.

The media viscosity has only little effect on the response time. Even at a viscosities up to 100 cSt, the response time will not exceed 4 ms.

Product specification

Technical data

Table 1: Performance (EN 60770)

Accuracy (incl. non-linearity, hysteresis and repeatability)	$\leq \pm 0.5\%$ FS (typ.) $\leq \pm 1.0\%$ FS (max.)	
Non-linearity BFSL (conformity)	$\leq \pm 0.2\%$ FS	
Hysteresis and repeatability	$\leq \pm 0.1\%$ FS	
Thermal error band (compensated temperature range)	$\leq \pm 1.0\%$ FS	
Response time	Liquids with viscosity < 100 cSt	< 4 ms
	Air and gases (MBS 3250)	< 35 ms
Overload pressure (static)	6 × FS (max. 1500 bar)	
Burst pressure	6 × FS (max. 2000 bar)	
Power-up time	< 50 ms	
Durability, P: 10 – 90% FS	> 10 × 10 ⁶ cycles	

Table 2: Electrical specifications

Nom. output signal (short-circuit protected)	4 – 20 mA	0 – 5 V, 1 – 5 V, 1 – 6 V DC	0 – 10 V, 1 – 10 V DC	10 – 90% of supply voltage
Supply voltage [U _b], polarity protected	9 – 32 V DC	9 – 32 V DC	15 – 32 V DC	4.5 – 5.5 V DC
Supply – current consumption	–	≤ 5 mA	≤ 8 mA	≤ 5 mA at 5 V DC
Supply voltage dependency	< 0.1% FS / 10 V	< 0.05% FS / 10 V		–
Ratiometricity	–	–		< 0.05% FS / 4.5 – 5.5 V
Output limitation	22.4 mA	0-5 V: 5.75 V, 1-5 V: 5.6 V, 1-6 V: 6.75 V	0-10 V: 11.5 V	≈ supply voltage
Sink / Source	–	< 1 mA		
Load [R _L] (load connected to 0 V)	$R_L \leq (U_b - 9 V) / 0.02 A$	$R_L \geq 10 k\Omega$	$R_L \geq 15 k\Omega$	$R_L \geq 10 k\Omega$ at 5 V DC

Table 3: Environmental conditions

Sensor operating temperature (depending on gasket material)	4 – 20 mA	-40 – 100 °C	
	10 – 90% of supply voltage 0 – 5 V, 1 – 5 V, 1 – 6 V, 0 – 10 V	-40 – 125 °C	
Media temperature range		-40 – 125 °C	
Ambient temperature range (depending on electrical connection)		See Electrical connections	
Compensated temperature range		0 – 100 °C	
Transport/storage temperature range		-50 – 125 °C	
EMC – Emission		EN 61000-6-3	
EMC – Immunity		EN 61000-6-2	
Insulation resistance		> 100 mΩ at 500 V DC	
Mains frequency test		Based on SEN 361503	
Vibration stability	Sinusoidal	15.9 mm-pp, 5 Hz – 25 Hz 20 g, 25 Hz – 2 kHz	IEC 60068-2-6
	Random	7.5 g _{rms} , 5 Hz – 1 kHz	IEC 60068-2-64
Shock resistance	Shock	500 g / 1 ms	IEC 60068-2-27
	Free fall	1 m	IEC 60068-2-32
Enclosure (depending on electrical connection)		See Electrical connections	

Table 4: Explosive atmospheres

Zone 2 applications ⁽¹⁾	 Ex ce IIA T3 Gc -10°C < Ta < +85°C	EN60079-0; EN60079-7
------------------------------------	---	----------------------

⁽¹⁾ When used in ATEX Zone 2 areas at low temperatures the cable and plug must be protected against impact.


Pressure transmitters, type MBS 3200 and MBS 3250

Table 5: Mechanical characteristics

Materials	Wetted parts	EN 10088-1; 1.4404 (AISI 316 L)
	Enclosure	EN 10088-1; 1.4404 (AISI 316 L)
	Electrical connections	See Electrical connections
	Pressure connection	See Dimensions/Combinations
Net weight (depending on pressure connection and electrical connection)		0.2 – 0.3 kg

Dimensions/Combinations

Type code	A1	G1	A3	E3	A8	C8
	EN175301-803-A Pg 9	AMP Econoseal	2 m screened cable	EN 60947-5-2 M12 x 1; 4-pin	AMP Superseal	ISO 15170-A1-3-2-Sn Bayonet



	G¼ A (EN 837)	G½ A (EN 837)	¼ - 18 NPT	½ - 14 NPT	DIN 3852-A-M 18 x 1.5	DIN 3852-E-G¼	DIN 3852-E-M 14 x 1.5	Din 3852-A-G 3/8
Type code	AB04	AB08	AC04	AC08	GA12	GB04	FA09	GB06
Recommended torque ⁽¹⁾	30 - 35 Nm	30 - 35 Nm	2-3 turns after finger tightened	2-3 turns after finger tightened	30 - 35 Nm	30 - 35 Nm	30 - 35 Nm	30 - 35 Nm

⁽¹⁾Depends on various parameters such as seal material, coupling material, thread lubrication and pressure level

Electrical connections

Table 6: Electrical connections

Type code	A1	G1	A3	E3	A8	C8
	EN 175301-803-A, Pg 9	AMP Econoseal J series (male)	2 m screened cable	EN 60947-5-2 M12 x 1; 4-pin	AMP Superseal 1.5 series (male)	ISO 15170-A1-3-2 Sn Bayonet
Ambient temperature 4 - 20 mA output	-40 – 100 °C	-30 – 100 °C	-30 – 85 °C	-25 – 90 °C	-30 – 100 °C	-40 – 100 °C
Ambient temperature 0 - 5 V, 1 - 5 V, 1 - 6 V, 0 - 10 V, 1 - 10 V output	-40 – 125 °C	-30 – 105 °C	-30 – 85 °C	-25 – 90 °C	-30 – 100 °C	-40 – 125 °C
Ambient temperature Ratiometric output, 10-80% of supply voltage	-40 – 125 °C	-30 – 105 °C	-30 – 85 °C	-25 – 90 °C	-30 – 100 °C	-40 – 125 °C
Enclosure (IP protection fulfilled together with mating connector)	IP65	IP67	IP67	IP67	IP67	IP67/IP69
Material	Glass filled polyamid, PA 6.6	Glass filled polyamid, PA 6.6 ⁽¹⁾	Poliolyfin cable with PE shrinkage tubing	Nickel plated brass, CuZn/Ni	Glass filled polyamid, PA 6.6 ⁽²⁾	Glass filled polyamid, PA 6.6 ⁽²⁾
Electrical connection, 4 – 20 mA output (2 wire)	Pin1: + supply Pin 2: ÷ supply Pin 3: not used Earth: Connected to MBS enclosure	Pin 1: + supply Pin 2: ÷ supply ⁽³⁾ Pin 3: not used	Brown wire: + supply Red wire: ÷ supply Red wire: not used Orange: not used Screen: not connected to MBS enclosure	Pin1: + supply Pin 2: not used Pin 3: not used Pin 4: ÷ supply	Pin1: + supply Pin 2: ÷ supply Pin 3: not used	Pin1: + supply Pin 2: ÷ supply Pin 3: not used Pin 4: not used
Electrical connection, 0 – 5 V, 1 – 5 V, 1 – 6 V, 0 – 10 V, 1 – 10 V output	Pin1: + supply Pin 2: ÷ supply Pin 3: + output Earth: Connected to MBS enclosure	Pin 1: + supply Pin 2: ÷ supply Pin 3: + output	Brown wire: + output Black wire: ÷ supply ⁽³⁾ Red wire: not used Orange: not used Screen: not connected to MBS enclosure	Pin 1: + supply Pin 2: not used Pin 3: + output Pin 4: ÷ supply ⁽³⁾	Pin 1: + supply Pin 2: ÷ supply ⁽³⁾ Pin 3: + output	-
Electrical connection Ratiometric output, 10-90% of supply voltage	Pin1: + supply Pin 2: ÷ supply Pin 3: output ⁽³⁾ Earth: Connected to MBS enclosure	Pin 1: + supply Pin 2: ÷ supply ⁽³⁾ Pin 3: + output	Brown wire: output Black wire: ÷ supply Red wire: + supply ⁽³⁾ Orange wire: not used Screen: not connected to MBS enclosure	Pin1: + supply Pin 2: not used Pin 3: output Pin 4: ÷ supply ⁽³⁾	Pin1: + supply Pin 2: ÷ supply Pin 3: output ⁽³⁾	Pin 1: + supply Pin 2: + output Pin 3: Ventilation Pin 4: ÷ supply ⁽³⁾

⁽¹⁾ Female plug: Glass filled polyester, PBT

⁽²⁾ Wire: PTFE (teflon) Protection sleeve: PBT mesh (polyester)

⁽³⁾ Common

Ordering

Ordering standard

MBS 3200 MBS 3250																																
Measuring range	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td>0 – 1.0 bar</td><td style="text-align: center;">10</td></tr> <tr><td>0 – 1.6 bar</td><td style="text-align: center;">12</td></tr> <tr><td>0 – 2.5 bar</td><td style="text-align: center;">14</td></tr> <tr><td>0 – 4.0 bar</td><td style="text-align: center;">16</td></tr> <tr><td>0 – 6.0 bar</td><td style="text-align: center;">18</td></tr> <tr><td>0 – 10 bar</td><td style="text-align: center;">20</td></tr> <tr><td>0 – 16 bar</td><td style="text-align: center;">22</td></tr> <tr><td>0 – 25 bar</td><td style="text-align: center;">24</td></tr> <tr><td>0 – 40 bar</td><td style="text-align: center;">26</td></tr> <tr><td>0 – 60 bar</td><td style="text-align: center;">28</td></tr> <tr><td>0 – 100 bar</td><td style="text-align: center;">30</td></tr> <tr><td>0 – 160 bar</td><td style="text-align: center;">32</td></tr> <tr><td>0 – 250 bar</td><td style="text-align: center;">34</td></tr> <tr><td>0 – 400 bar</td><td style="text-align: center;">36</td></tr> <tr><td>0 – 600 bar</td><td style="text-align: center;">38</td></tr> </table>	0 – 1.0 bar	10	0 – 1.6 bar	12	0 – 2.5 bar	14	0 – 4.0 bar	16	0 – 6.0 bar	18	0 – 10 bar	20	0 – 16 bar	22	0 – 25 bar	24	0 – 40 bar	26	0 – 60 bar	28	0 – 100 bar	30	0 – 160 bar	32	0 – 250 bar	34	0 – 400 bar	36	0 – 600 bar	38	Gasket/O-ring material
0 – 1.0 bar	10																															
0 – 1.6 bar	12																															
0 – 2.5 bar	14																															
0 – 4.0 bar	16																															
0 – 6.0 bar	18																															
0 – 10 bar	20																															
0 – 16 bar	22																															
0 – 25 bar	24																															
0 – 40 bar	26																															
0 – 60 bar	28																															
0 – 100 bar	30																															
0 – 160 bar	32																															
0 – 250 bar	34																															
0 – 400 bar	36																															
0 – 600 bar	38																															
		<table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td>0</td><td>No gasket (see pressure connections)</td></tr> <tr><td>1</td><td>Viton (media temp.: -20 – 125 °C)</td></tr> <tr><td>3</td><td>O-ring, Viton (media temp.: -20 – 125 °C)</td></tr> </table>	0	No gasket (see pressure connections)	1	Viton (media temp.: -20 – 125 °C)	3	O-ring, Viton (media temp.: -20 – 125 °C)																								
0	No gasket (see pressure connections)																															
1	Viton (media temp.: -20 – 125 °C)																															
3	O-ring, Viton (media temp.: -20 – 125 °C)																															
		Pressure connection																														
		<table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td>A B 0 4</td><td>G ¼ A (EN837) (MBS 3200)</td></tr> <tr><td>A B 0 8</td><td>G½ A (EN837)</td></tr> <tr><td>A C 0 4</td><td>¼ - 18 NPT</td></tr> <tr><td>A C 0 8</td><td>½ - 14 NPT (MBS 3200)</td></tr> <tr><td>G A 1 2</td><td>DIN 3852-A M18 × 1.5</td></tr> <tr><td>G B 0 4</td><td>DIN 3852-E-G ¼</td></tr> <tr><td>F A 0 9</td><td>DIN 3852-E-M 14 × 1.5</td></tr> <tr><td>G B 0 6</td><td>DIN 3852-A-G ⅜</td></tr> </table>	A B 0 4	G ¼ A (EN837) (MBS 3200)	A B 0 8	G½ A (EN837)	A C 0 4	¼ - 18 NPT	A C 0 8	½ - 14 NPT (MBS 3200)	G A 1 2	DIN 3852-A M18 × 1.5	G B 0 4	DIN 3852-E-G ¼	F A 0 9	DIN 3852-E-M 14 × 1.5	G B 0 6	DIN 3852-A-G ⅜														
A B 0 4	G ¼ A (EN837) (MBS 3200)																															
A B 0 8	G½ A (EN837)																															
A C 0 4	¼ - 18 NPT																															
A C 0 8	½ - 14 NPT (MBS 3200)																															
G A 1 2	DIN 3852-A M18 × 1.5																															
G B 0 4	DIN 3852-E-G ¼																															
F A 0 9	DIN 3852-E-M 14 × 1.5																															
G B 0 6	DIN 3852-A-G ⅜																															
Pressure reference	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td>Gauge (relative)</td><td style="text-align: center;">1</td></tr> <tr><td>Absolute</td><td style="text-align: center;">2</td></tr> </table>	Gauge (relative)	1	Absolute	2	Electrical connection																										
Gauge (relative)	1																															
Absolute	2																															
		<table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td>A1</td><td>Plug, EN 175301-803-A, Pg 9</td></tr> <tr><td>G1</td><td>* Plug, AMP Econoseal, J Series, male, excl. female plug</td></tr> <tr><td>A3</td><td>Screened cable , 2 m</td></tr> <tr><td>E3</td><td>* Plug, EN 60947-5-2, M12 x 1, male, excl. female plug</td></tr> <tr><td>A8</td><td>* Plug, AMP Superseal, 1.5 Series, male, excl. female plug</td></tr> <tr><td>C8</td><td>Plug, ISO 15170-A1-3.2-Sn male, excl. female plug, Bayonet</td></tr> </table>	A1	Plug, EN 175301-803-A, Pg 9	G1	* Plug, AMP Econoseal, J Series, male, excl. female plug	A3	Screened cable , 2 m	E3	* Plug, EN 60947-5-2, M12 x 1, male, excl. female plug	A8	* Plug, AMP Superseal, 1.5 Series, male, excl. female plug	C8	Plug, ISO 15170-A1-3.2-Sn male, excl. female plug, Bayonet																		
A1	Plug, EN 175301-803-A, Pg 9																															
G1	* Plug, AMP Econoseal, J Series, male, excl. female plug																															
A3	Screened cable , 2 m																															
E3	* Plug, EN 60947-5-2, M12 x 1, male, excl. female plug																															
A8	* Plug, AMP Superseal, 1.5 Series, male, excl. female plug																															
C8	Plug, ISO 15170-A1-3.2-Sn male, excl. female plug, Bayonet																															
Output signal	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td>4 – 20 mA</td><td style="text-align: center;">1</td></tr> <tr><td>0 – 5 V</td><td style="text-align: center;">2</td></tr> <tr><td>1 – 5 V</td><td style="text-align: center;">3</td></tr> <tr><td>1 – 6 V</td><td style="text-align: center;">4</td></tr> <tr><td>0 – 10 V</td><td style="text-align: center;">5</td></tr> <tr><td>1 – 10 V</td><td style="text-align: center;">7</td></tr> <tr><td>10 - 90% of supply</td><td style="text-align: center;">6</td></tr> </table>	4 – 20 mA	1	0 – 5 V	2	1 – 5 V	3	1 – 6 V	4	0 – 10 V	5	1 – 10 V	7	10 - 90% of supply	6																	
4 – 20 mA	1																															
0 – 5 V	2																															
1 – 5 V	3																															
1 – 6 V	4																															
0 – 10 V	5																															
1 – 10 V	7																															
10 - 90% of supply	6																															
* Gauge versions only available as sealed gauge versions																																
<div style="display: flex; align-items: center;"> <div style="width: 15px; height: 15px; background-color: #ccc; margin-right: 5px;"></div> Preferred version </div>																																

NOTE:

Non-standard build-up combinations may be selected. However, minimum order quantities may apply. Please contact your local Danfoss office for further information or request on other versions.

Certificates, declarations and approvals

The list contains all certificates, declarations, and approvals for this product type. Individual code number may have some or all of these approvals, and certain local approvals may not appear on the list.

Some approvals may change over time. You can check the most current status at danfoss.com or contact your local Danfoss representative if you have any questions.

Valid certificates and declarations

File name	Document type	Document topic	Approval authority
E227388	Explosive - Safety Certificate	Hazardous Locations	UL
E31024	Electrical - Safety Certificate	-	UL
E311982	Electrical - Safety Certificate	-	UL
DK.C.30.018.A 31316	Measuring - Performance Certificate	-	GOST
064G9615.06	EU Declaration	ATEX/EMCD/RoHS	Danfoss
CN.C.30.004.A 59728-1	Measuring - Performance Certificate	-	GOST
CRN.OF18477.5123467890YTN	Pressure - Safety Certificate	CRN	TSSA
060R3160.00	Manufacturers Declaration	China RoHS	Danfoss
064R9402.00	Manufacturers Declaration	PED	Danfoss
E494625	Electrical - Safety Certificate	-	UL
1786330	Explosive - Safety Certificate	-	CSA

Online support

Danfoss offers a wide range of support along with our products, including digital product information, software, mobile apps, and expert guidance. See the possibilities below.

The Danfoss Product Store



The Danfoss Product Store is your one-stop shop for everything product related—no matter where you are in the world or what area of the cooling industry you work in. Get quick access to essential information like product specs, code numbers, technical documentation, certifications, accessories, and more.

Start browsing at store.danfoss.com.

Find technical documentation



Find the technical documentation you need to get your project up and running. Get direct access to our official collection of data sheets, certificates and declarations, manuals and guides, 3D models and drawings, case stories, brochures, and much more.

Start searching now at www.danfoss.com/en/service-and-support/documentation.

Danfoss Learning



Danfoss Learning is a free online learning platform. It features courses and materials specifically designed to help engineers, installers, service technicians, and wholesalers better understand the products, applications, industry topics, and trends that will help you do your job better.

Create your Danfoss Learning account for free at www.danfoss.com/en/service-and-support/learning.

Get local information and support



Local Danfoss websites are the main sources for help and information about our company and products. Find product availability, get the latest regional news, or connect with a nearby expert—all in your own language.

Find your local Danfoss website here: www.danfoss.com/en/choose-region.

Spare Parts



Get access to the Danfoss spare parts and service kit catalog right from your smartphone. The app contains a wide range of components for air conditioning and refrigeration applications, such as valves, strainers, pressure switches, and sensors.

Download the Spare Parts app for free at www.danfoss.com/en/service-and-support/downloads.

Coolselector®2 - find the best components for you HVAC/R system



Coolselector®2 makes it easy for engineers, consultants, and designers to find and order the best components for refrigeration and air conditioning systems. Run calculations based on your operating conditions and then choose the best setup for your system design.

Download Coolselector®2 for free at coolselector.danfoss.com.

Any information, including, but not limited to information on selection of product, its application or use, product design, weight, dimensions, capacity or any other technical data in product manuals, catalogues descriptions, advertisements, etc. and whether made available in writing, orally, electronically, online or via download, shall be considered informative, and is only binding if and to the extent, explicit reference is made in a quotation or order confirmation. Danfoss cannot accept any responsibility for possible errors in catalogues, brochures, videos and other material. Danfoss reserves the right to alter its products without notice. This also applies to products ordered but not delivered provided that such alterations can be made without changes to form, fit or function of the product. All trademarks in this material are property of Danfoss A/S or Danfoss group companies. Danfoss and the Danfoss logo are trademarks of Danfoss A/S. All rights reserved.