



Description: Standard door equipped with double-bit 3 mm lock system and door frame. Door accessory kit DNMK (hinges, rod catches) to be ordered separately. Allows all the options of the locking program and 180° hinges. Compatible with combinable and compact enclosure ranges.

Material: 2 mm steel plate.

Maximum load: 800 N.

Finish: RAL 7035 structured powder coating.

Mounting requirements: Use hinge kit DNMK if no door was fitted previously.

Pack quantity: 1 piece.

Plain door

| H | W | Item no. |
|------|------|----------|
| 1100 | 600 | DN1106R5 |
| 1200 | 600 | DN1206R5 |
| 1200 | 800 | DN1208R5 |
| 1400 | 600 | DN1406R5 |
| 1400 | 800 | DN1408R5 |
| 1600 | 600 | DN1606R5 |
| 1600 | 800 | DN1608R5 |
| 1600 | 1000 | DN1610R5 |
| 1800 | 500 | DN1805R5 |
| 1800 | 600 | DN1806R5 |
| 1800 | 800 | DN1808R5 |
| 1800 | 1000 | DN1810R5 |
| 2000 | 500 | DN2005R5 |
| 2000 | 600 | DN2006R5 |
| 2000 | 800 | DN2008R5 |
| 2000 | 1000 | DN2010R5 |
| 2200 | 600 | DN2206R5 |
| 2200 | 800 | DN2208R5 |

Left door

| H | W | Item no. |
|------|-----|-----------|
| 1200 | 600 | DN1206LR5 |
| 1400 | 500 | DN1405LR5 |
| 1400 | 600 | DN1406LR5 |
| 1600 | 600 | DN1606LR5 |
| 1800 | 400 | DN1804LR5 |
| 1800 | 500 | DN1805LR5 |
| 1800 | 600 | DN1806LR5 |
| 1800 | 800 | DN1808LR5 |
| 2000 | 400 | DN2004LR5 |
| 2000 | 500 | DN2005LR5 |
| 2000 | 600 | DN2006LR5 |
| 2000 | 800 | DN2008LR5 |
| 2200 | 500 | DN2205LR5 |
| 2200 | 600 | DN2206LR5 |