

CUS

SLIM-IN MOUNTING COOLING UNITS



Description: High performance cooling unit for vertical installation. Partially recessed installation, providing effective use of space in front and side mounting. The cooling capacity range is from 850W to 2500 W, with only 3 different cut-outs. Common to all models is the self cleaning condenser coil which eliminates the necessity for an air filter and therefore avoiding ordinary maintenance. In the Slim units the electronic controller is standard. The thermostat is adjustable between 25°C and 45°C, factory setting 35°C (set point can be modified directly from the electronic controller). Cooling capacity shown in the table is at L35/L35, the cooling capacity for specific conditions are indicated in the diagrams. Ozone friendly refrigerant R134a.

Type of connection: Spring-type terminal included

Material: Mild steel

Temperature limits inside: 25°C to 45°C.

Temperature limits outside: 20°C to 55°C.

Protection degree: IP 54 towards the enclosure, and IP 34 towards the surroundings.

Finish: RAL 7035.

Approvals: CE, UL "for USA and Canada"



| Capacity (W) | | Current (A) | Noise (dB) | Item no. |
|--------------|-------------------|-------------|------------|----------|
| 850 | 230-1-50/60 | 2,0 | 65 | CUS08502 |
| 1400 | 230-1-50/60 | 4,0 | 65 | CUS14002 |
| 2000 | 230-1-50/60 | 7,0 | 65 | CUS20002 |
| 2500 | 400-3-50 460-3-60 | 3,6 | 65 | CUS25004 |