

Description: For full height mounting of swing frames in MultiFlex enclosures. When partial height mounting is required use the SFB in combination with CLPK or CLPF. The swing frames can be mounted both left and right hand opening. One man installation with integrated safety catch which holds the swing frame in mounting position (130° hinge). Supplied with aligning wheel for automatic positioning of the swing frame. Pre-punched holes for mounting a door switch (DSW01) and enclosure light (LTL14xx) are provided in the top swing frame support with W>600mm and with SFS or SFM swing frames.

Material: 3mm zinc plated steel.

Pack quantity: One complete kit for a swing frame.

Mounting requirement: Support bars (SFB) 600mm wide can also be mounted directly into a 1200mm wide enclosure by means of a VBD. Support bars (SFB) 800mm wide can also be mounted directly in 1600mm wide enclosures.

For enclosure		For enclosure	
For enclosure	н	W	Item no.
MM/MF	1200/1600/2000	600	SFB0612
	1400/1800/2200	600	SFB0614
	1200/1600/2000	800	SFB0812
	1400/1800/2200	800	SFB0814
	1200/1600/2000	1000	SFB1012
	1400/1800/2200	1000	SFB1014
	1200/1600/2000	1200	SFB1212
	1400/1800/2200	1200	SFB1214

