SFC

FULL HEIGHT SWING FRAME



Description: Full height swing frame for 19" components allowing left and right hand opening. Can be used in MultiFlex enclosures. Hinges designed to give extra build-in depth. Adjustable top hinge for square mounting of the swing frame. Rigid W-shaped frame profile for heavy equipment. Zinc plated frame for direct earthing of the mounted components. Standard equipped with 130° hinges (180° hinges not applicable for 600mm wide enclosures). Can also be mounted on the side of 600mm deep floor standing enclosures. For MultiFlex use transversal support bars SFB in combination with VBD if required. Adjustable in depth by steps of 12.5mm. Vertical profiles, 2mm and horizontal profiles, 3mm.

Lock: Two 3mm double-bit locks.

Material: Zinc plated steel.

Pack quantity: 1 swing frame with hinges.

Mounting requirement: SFC for 600mm, 800mm, 1000mm, 1200mm wide MultiFlex enclosures. Add SFB for mounting in a MultiFlex enclosure.

	For				
U	Н	H1	H2	Н3	Item no.
27	1400	1203	1267	1337	SFC276
31	1600	1381	1445	1515	SFC316
36	1800	1603	1667	1737	SFC366
40	2000	1781	1845	1915	SFC406
45	2200	2003	2067	2137	SFC456

