

Fuse enclosure, 1xdisconnector 3p NH1 250A, HxWxD=375x375x150mm

Powering Business Worldwide™

Part no. **GSTA1/I44** Article no. 013163

Delivery program

Dimensions		mm	95 95 95
Product range			Ci insulated enclosures
Basic function			Enclosures with devices fitted
Product function			Distribution board enclosure with NH fuse switch-disconnector
Single unit/Complete unit			Stand-alone device
Degree of Protection			IP65
Description			Sides closed, but with full area knockout Open top and bottom Sealable cover fasteners Fuse switch-disconnector fitted to steel mounting plate Mounting plate protruding 50 mm Terminal for connecting the 4th conductor (PEN)
Type cover			Transparent
Width		mm	375
Height		mm	375
Fuse cartridge		Size	NH1
Rated operational current	I _e	Α	250 200
Rated operational voltage	U _e	V AC	500 660 690
consists of			
Basic enclosure			C144-200
Mounting system			L1-Cl44
Base unit		BxHxD	GSTA1
Accessories			HS 50-CI

Notes Stepped cable grommets →#057621

Fuse links

- →#288934 →#288909 →#100651

Additional product information (links)

Manufacturer's Declaration CI-RoHS	ftp://ftp.moeller.net/DOCUMENTATION/PDF/2013-01-31_Ci_RoHS.pdf
Declaration of conformity	ftp://ftp.moeller.net/DOCUMENTATION/PDF/ci_ce.pdf