



Set of clamp-type terminals f. GST2, 120-240mm²

Part no. **PSK2**
 Catalog No. **043480**

Delivery program

Product range		60 mm system
Subrange		Sets of clamp-type terminals
Information about equipment supplied		One set comprises 3 clamp-type terminals
Clamping range		1 x (120 - 240) mm ² Cu/Al
For use with		GSU2, GST...2

Technical data

Electrical

Direction of incoming supply		as required
------------------------------	--	-------------

Mechanical

Climatic proofing		Damp heat, constant, to IEC 60068--2--3 Damp heat, cyclical, to IEC 60068--2--30
Mounting position		Vertical or horizontal

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Busbar terminal (EC000001)		
Electric engineering, automation, process control engineering / Electrical installation, device / Terminal (not overhead line) / Switch board (ecl@ss10.0.1-27-14-11-46 [BAA025013])		
Busbar thickness	mm	0 - 0
Busbar width	mm	60 - 60
Suitable for		Other
Width clamp	mm	0
Max. conductor cross section	mm ²	240
Max. rated operation current I _e	A	0
Suitable for round conductor connection		Yes
Suitable for sector conductor connection		No
Suitable for strip conductor connection		No