



**Handle, for lateral lever lockable, red, NEMA 12**

**Part no. NZM-XSHGVR12-NA**  
**Article no. 107269**

**Delivery programme**

		Handle, metal, silver/red
		Degree of protection UL/CSA Type 12
Product range		Accessories
Accessories		Side mounted handle for North America
Standard/Approval		UL/CSA
Construction size		NZM2
Description		For mounting outside the control panel door. Actuation of a switch with toggle lever using a Bowden cable and mechanical components mounted on the front end of the switch. For switch with toggle lever  <b>Attention! Intended exclusively for use outside the scope of validity of IEC/EN 60947.</b>
For use with		NZM2...-NA, NS2...-NA NZM3...-NA, NS3...-NA
<b>Notes</b>		
Lockable in 0-position on handle with up to 3 padlocks, for 1 door of an American style control panel door (door plus wide bar beside the door).		
For each handle 1 additional mechanical unit and 1 Bowden cable is required		

**Approvals**

Product Standards		UL489; CSA-C22.2 No. 5-09
UL File No.		E140305
UL Category Control No.		DIHS
CSA File No.		236770
CSA Class No.		1437-01
North America Certification		UL listed, CSA certified
Specially designed for North America		NA style Flange Mount: vertical motion handle and flex cable assembly, compliant with requirements for the Supply Circuit Disconnecting Means per NFPA79 and UL 508A Industrial Machinery standards.
Degree of Protection		IEC: IP66, UL/CSA Type 12