

## Intruder alarm panel

Katalog Nr.      I-ON160EXS

## Delivery program

Users			500
Back Up Battery Maximum Size			17Ah
Shunt Groups			0
Out Of The Box Radio Zones			0
Wired External Sounders			1
Integrated Dial Device			No
Emergency Power Supply Integrated			Yes
Out Of The Box Wired Zones			10
Number Of Keypads			45
With Power Adaptor			No
Suitable For Bus Connection			Yes
Max Areas (Partitions/Wards)			20
Total Capacity Zones			160
Cloud Support			No
Supports ARD			Yes
On Board Outputs (Panel)			4
EN 50131 Security Grade			2 or 3
Wired Internal Sounders			2
Web Browser Interface			Yes
Number Of Indicator Groups			160
Power Supply Size			3.0A
Number Of Sabotage Groups			46
Operating Voltage		V	230
Radio External Sounders			0
Log Events			2000
Occurrence Memory			Yes
Radio Connection			No
Custom Outputs			0
Max 1-Way Radio Keypads			20
Back Up Battery Quantity			2
Communications Options			On Board Ethernet. Plug on GSM, PSTN
Number Of Outputs For Optical Signal Generators			20
VdS Class			None
Number Of Bus Devices			45
Radio Internal Sounders			0
On Board Outputs (Plug By)			16
Connection			Hybrid
ETIM Class			EC001525

## Technical data ETIM 7.0

Alarmanlagen, Notruf- und Meldesysteme (EG000054) / Einbruchmeldezentrale (EC001525)			
Elektro-, Automatisierungs- und Prozessleittechnik / Objekt-, Zutrittsüberwachungssystem / Intrusionsschutztechnik/Einbruchmeldetechnik / Einbruchmeldezentrale (ecl@ss10.0.1-27-39-02-01 [ABS531008])			
Anzahl der Meldegruppen			

Anzahl der Sabotagegruppen			
Anzahl der Überfallgruppen			500
Integriertes Wählgerät			
Anzahl der Ausgänge für akustische Signalgeber			
Anzahl der Ausgänge für optische Signalgeber			
Ereignisspeicher			
Betriebsspannung		V	
Busfähig			
Funkanbindung			
Mit Netzteil			
Notstromversorgung integriert			
Schnittstelle extern			
VdS Klasse			
Höhe		mm	427
Breite		mm	420
Tiefe		mm	85