



Door, IP40, for HxW=1400x600mm

Part no. XVTL-D-6-14

Catalog No. 114635

EL-Nummer (Norway) 2460050

Delivery program

| | | |
|--------------------------------------|--|---|
| Product range | | Control centres XVTL |
| Basic function | | Combination enclosures |
| Product function | | Accessories |
| Accessories | | Doors |
| Single unit/Complete unit | | Modular system |
| Description | | Closed Single wing door 3-point turn lock with roller lever lock |
| Material | | Sheet steel 1.25 mm |
| Surface finish | | Polyester powder coating RAL 7035, light grey RAL 9016, traffic white |
| Information about equipment supplied | | Including screws |
| Protection type | | IP55 |
| Suitable for width | | 600 |
| Suitable for height | | 1400 |

Technical data ETIM 6.0

| | | |
|--|----|---------------------|
| Cabinet enclosures (EG000011) / Door/operating panel (switchgear cabinet) (EC000747) | | |
| Electric engineering, automation, process control engineering / Electrical cabinet, housing, rack / Door (electrical cabinet) / Door/operating panel (enclosure) (ecl@ss8.1-27-18-22-04 [ACN614008]) | | |
| Model | | Stop door |
| Version as glazed door | | No |
| Version as door for disconnecting switch interlocking | | No |
| Width | mm | 593 |
| Height | mm | 1340 |
| Depth | mm | 40 |
| EMC-version | | Yes |
| Material | | Steel |
| Type of surface | | With powder coating |
| Colour | | Grey |
| Degree of protection (IP) | | IP55 |