# DATASHEET - XVTL-D-8-18

**Door, IP40, for HxW=1800x800mm**

| | |
|---|---|
| **Part no.** | **XVTL-D-8-18** |
| **Catalog No.** | **114644** |
| **EL-Nummer (Norway)** | **2460059** |

## Delivery program

| | | |
|---|---|---|
| Product range | | Control centres XVTL |
| Basic function | | Combination enclosures |
| Product function | | Accessories |
| Accessories | | Doors |
| Single unit/Complete unit | | Modular system |
| Description | | Closed<br>Single wing door<br>3-point turn lock with roller lever lock |
| Material | | Sheet steel 1.25 mm |
| Surface finish | | Polyester powder coating<br>RAL 7035, light grey<br>RAL 9016, traffic white |
| Information about equipment supplied | | Including screws |
| Protection type | | IP55 |
| Suitable for width | | 800 |
| Suitable for height | | 1800 |

## Technical data ETIM 7.0

Cabinet enclosures (EG000011) / Door/operating panel (switchgear cabinet) (EC000747)

Electric engineering, automation, process control engineering / Electrical cabinet, housing, rack / Door (electrical cabinet) / Door/operating panel (enclosure) (ecl@ss10.0.1-27-18-22-04 [ACN614011])

| | | |
|---|---|---|
| Model | | Stop door |
| Version as glazed door | | No |
| Version as door for disconnecting switch interlocking | | No |
| Width | mm | 793 |
| Height | mm | 1740 |
| Depth | mm | 40 |
| EMC-version | | Yes |
| Material | | Steel |
| Surface finishing | | Powder coating |
| Colour | | Grey |
| Degree of protection (IP) | | IP55 |
| Degree of protection (NEMA) | | |