DATASHEET - XVTL-D-12-18-L



Door, left, for HxW=1800x1200mm

Part no. Catalog No. XVTL-D-12-18-L 114648

2460063

EL-Nummer (Norway)



Delivery program

Product range	Control centres XVTL
Basic function	Combination enclosures
Product function	Accessories
Accessories	Doors
Single unit/Complete unit	Modular system
Description	Closed Single wing door 3-point turn lock with roller lever lock
Material	Sheet steel 1.25 mm
Surface finish	Polyester powder coating RAL 7035, light grey RAL 9016, traffic white
Information about equipment supplied	can be used as left door for two-leaf versions order left and right door leaf separately Including screws
Protection type	IP55
Suitable for width	1200
Suitable for height	1800
	Protective cover mounted on left

Technical data ETIM 6.0

Cabinet enclosures (EG000011) / Door/operating panel (switchgear cabinet) (EC000747)

Electric engineering, automation, process control engineering / Electrical cabinet, housing, rack / Door (electrical cabinet) / Door/operating panel (enclosure) (ecl@ss8.1-27-18-22-04 [ACN614008])

Version as glazed door Image: Marcine Stream of the Stream o			
Arrow Arrow <th< td=""><td>Model</td><td></td><td>Stop door</td></th<>	Model		Stop door
Widthmm593Heightmm1740Depthmm40EMC-versionMmVesMaterialMmStelType of surfaceMmVith powder coatingColourMmMm	Version as glazed door		No
Heightnm740Depthnm40EMC-versionrm40MaterialresresType of surfaceresresColourresresStateresres<	Version as door for disconnecting switch interlocking		No
Depth mm 40 EMC-version Imm 40 Material Imm Yes Type of surface Imm Steel Colour Imm Imm	Width	mi	mm 593
EMC-version Yes Material Steel Type of surface With powder coating Colour Grey	Height	mi	mm 1740
Material Steel Type of surface With powder coating Colour Grey	Depth	mi	mm 40
Type of surface With powder coating Colour Grey	EMC-version		Yes
Colour Grey	Material		Steel
	Type of surface		With powder coating
Degree of protection (IP) IP55	Colour		Grey
	Degree of protection (IP)		IP55