DATASHEET - BP-U-3S-800/10-EW-W



3-step flush-mounting door frame with sheet steel door and rotary door handle, fireproof, W800mm H1060mm, white



Part no. BP-U-3S-800/10-EW-W

Catalog No. 116604

EL-Nummer 0002460457

(Norway)

Delivery program

with door Material Material Moor interlock Moor interlock Motor	zonro., program		
Material Sheet steel Door interlock Three-point turn-lock Installation site Indoor Degree of Protection IP30 Dire resistance Fire-resistant (E60/EW60) Durface finish With powder coating Durface for width INDOOR I	Mounting type		Flush mounted
Three-point turn-lock Indoor Indoor Indoor IP30 Irree-resistant (E60/EW60) Irreface finish Irree-point turn-lock Indoor IP30 Irree-resistant (E60/EW60) Irree-point turn-lock Indoor Irree-point turn-lock Indoor Irree-resistant (E60/EW60)	Features		with door
Indoor legree of Protection IP30 ire resistance ire resistance ire finish ire the sixtance in	Material		Sheet steel
Degree of Protection IP30 sire resistance fire-resistant (E60/EW60) Surface finish With powder coating 800	Door interlock		Three-point turn-lock
fire-resistant (E60/EW60) Furface finish Fur	Installation site		Indoor
Surface finish With powder coating width mm 800	Degree of Protection		IP30
Suitable for width mm 800	Fire resistance		fire-resistant (E60/EW60)
	Surface finish		With powder coating
olour white (RAL 9016)	Suitable for width	mm	800
	Colour		white (RAL 9016)

Technical data ETIM 7.0

Cabinet enclosures (EG000011) / Door/operating panel (switchgear cabinet) (EC000747)

Electric engineering, automation, process control engineering / Electrical cabinet, housing, rack / Door (electrical cabinet) / Door/operating panel (enclosure) (ecl@ss10.0.1-27-18-22-04 [ACN614011])

[ACN614011])		
Model		Stop door
Version as glazed door		No
Version as door for disconnecting switch interlocking		No
Width	mm	835
Height	mm	1060
Depth	mm	70
EMC-version		Yes
Material		Steel
Surface finishing		Powder coating
Colour		White
Degree of protection (IP)		IP30
Degree of protection (NEMA)		-