



**Surface-mount service distribution board with three-point turn-lock, fire-resistant, W 600 mm H 1260 mm**



**Part no. BP-O-600/12-EW**  
**Catalog No. 116622**

**EL-Nummer (Norway) 0002460475**

**Delivery program**

Mounting type			Surface mounted
Material			Sheet steel
Door interlock			Three-point turn-lock
Installation site			Indoor
Degree of Protection			IP30
Fire resistance			fire-resistant (E60/EW60)
Surface finish			With powder coating
Width		mm	600
Depth		mm	262
Height		mm	1260
Colour			light gray (RAL 7035)

**Design verification as per IEC/EN 61439**

Technical data for design verification			
Heat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890			
Individual enclosure for wall mounting	P <sub>V</sub>	CO	80
Starting enclosure for wall mounting	P <sub>V</sub>	CO	75
Middle enclosure for wall mounting	P <sub>V</sub>	CO	71
Heat dissipation, at an ambient temperature of 35°C, delta T: 35 degrees in top of the enclosure, calculated as per IEC 60890			
Individual enclosure for wall mounting	P <sub>V</sub>	CO	161
Starting enclosure for wall mounting	P <sub>V</sub>	CO	151
Middle enclosure for wall mounting	P <sub>V</sub>	CO	143
IEC/EN 61439 design verification			
10.2 Strength of materials and parts			
10.2.2 Corrosion resistance			Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures			Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat			Meets the product standard's requirements.
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects			Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation			Not relevant to indoor installations.
10.2.5 Lifting			Does not apply to enclosures without lifting aids.
10.2.6 Mechanical impact			IK07
10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of ASSEMBLIES			IP30
10.4 Clearances and creepage distances			Is the panel builder's responsibility.
10.5 Protection against electric shock			< 0.1 Ω; meets the product standard's requirements.
10.6 Incorporation of switching devices and components			Is the panel builder's responsibility.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9 Insulation properties			
10.9.2 Power-frequency electric strength			U <sub>i</sub> = 440 V AC
10.9.3 Impulse withstand voltage			4 kV
10.9.4 Testing of enclosures made of insulating material			Does not apply to metal enclosures.

10.10 Temperature rise			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating			Is the panel builder's responsibility.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility.
10.13 Mechanical function			Meets the product standard's requirements.

## Technical data ETIM 7.0

Distribution boards (EG000023) / Small distribution board (EC000214)

Electric engineering, automation, process control engineering / Electrical installation, device / Electrical distribution system (incl. small distribution board) / Small distribution board (ec1@ss10.0.1-27-14-24-09 [ACN387011])

Mounting method			Surface mounted (plaster)
Number of rows			9
Width in number of modular spacings			24
Type of cover			Door
Cover model			Closed
Transparent cover/door			No
Material housing			Steel
Height		mm	1260
Width		mm	600
Depth		mm	262.5
Built-in depth		mm	0
Internal depth		mm	257.5
DIN-rail			No
With mounting plate			No
Extension possible			Yes
EMC-version			No
Colour			Grey
RAL-number			7035
Degree of protection (IP)			IP30
With lock			No
Type of closure			Other