



Cassette 2500A, IZMX403 without control cable connection

Part no. IZMX-CAS403-2500
Catalog No. 122883

EL-Nummer (Norway) 0004357785

Delivery program

Accessories			Withdrawable units
Accessories			Cassettes
Rated current	I_n	A	2500
Rated ultimate short-circuit breaking capacity	I_{cu}	kA	65
Pole			3
For use with			IZMX40...3-...W INX40...3-...W
Instructions			Without terminal blocks for the control circuit terminals. Please order the required quantity separately.
Information about equipment supplied			with arcing chamber cover
Notes			
Without control circuit terminals			

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	70

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Chassis part power circuit breaker (EC002043)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Chassis part circuit breaker (ecl@ss10.0.1-27-37-04-22 [ACN955011])			
Rated current I_n		A	2500
Number of poles			3
Version as busbar adapter			No
Version as built-in device			Yes
Type of electrical connection of main circuit			Rail connection