



Spring release, 208-250VAC/DC

Part no. IZM-SR230AD  
 Catalog No. 122945  
 Eaton Catalog No. 2A10704G04  
 EL-Nummer 4357835  
 (Norway)

### Delivery program

Product range			Accessories
Current Range			4000 to 6300 A
Accessories			Voltage release
Accessories			Closing releases
Standard/Approval			IEC
			A closing release can be combined with a shunt release and an undervoltage release or with an undervoltage release or with a second shunt release.
Rated control voltage	$U_s$	V	220 - 250 DC 208 - 240 AC
For use with			IZM20, 32, 40, 63... IN20, 32,40, 63...
Instructions			If ordered separately a secondary terminal unit IZM-SEC-... is necessary for connection. Order separately if required. Terminal assignment page 71

### Technical data

#### Rated control voltage

AC 50/60 Hz	$U_s$	V	208 - 240
DC	$U_s$	V	220 - 250

#### Power consumption

AC		VA	(pick-up 450)
DC		W	(pick-up 450)
Circuit-breaker response time at $U_s$		ms	40

#### Operating range

Pick-up voltage		$x U_s$	
	Pick-up	$x U_c$	According to the IEC standard

### Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	70