DATASHEET - IZMX-CAS164-1600-SEC



Cassette 1600A, IZMX164 m. control cable connection

0004357987

IZMX-CAS164-1600-SEC 124175 Powering Business Worldwide"

EL-Nummer (Norway)

Part no. Catalog No.

Delivery program

Product range			Accessories
Accessories			Withdrawable units
Accessories			Cassettes
			Equipment supplied: arcing chamber cover, coding to basic device
Rated current	In	А	1600
Pole			4
For use with			IZMX164W INX164W
Instructions			Fully equipped with control circuit terminals
Information about equipment supplied			with arcing chamber cover
			Control circuit terminal
Notes			

Including complete set of control terminals

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.	٥	°C	-25
Operating ambient temperature max.	0	°C	70

Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Chassis part power circuit breaker (EC002043)					
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Chassis part circuit breaker (ecl@ss10.0.1-27-37-04-22 [ACN955011])					
Rated current In		А	1600		
Number of poles			4		
Version as busbar adapter			No		
Version as built-in device			Yes		
Type of electrical connection of main circuit			Rail connection		