



Reset remote, 110-125VAC/DC

Part no. IZMX-RR110AD-40  
 Catalog No. 124302

### Delivery program

Product range			Accessories
Accessories			Trip indication / Reset options
Accessories			Remote reset
			AC
Rated control voltage	U <sub>s</sub>	V	110 - 127 V AC 50/60 Hz 110 - 125 V DC
For use with			IZMX16...W IZMX40...W IZMX16...F IZMX40...F

### Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	70

### Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Shunt release (for power circuit breaker) (EC001023)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Full load current trip (ecl@ss10.0.1-27-37-04-18 [AKF016013])			
Rated control supply voltage U <sub>s</sub> at AC 50HZ		V	110 - 127
Rated control supply voltage U <sub>s</sub> at AC 60HZ		V	110 - 127
Rated control supply voltage U <sub>s</sub> at DC		V	110 - 125
Voltage type for actuating			AC/DC
Initial value of the undelayed short-circuit release - setting range		A	0
End value adjustment range undelayed short-circuit release		A	0
Type of electric connection			Flat plug-in connection
Number of contacts as normally open contact			0
Number of contacts as normally closed contact			0
Number of contacts as change-over contact			0
Suitable for power circuit breaker			Yes
Suitable for off-load switch			Yes
Suitable for motor safety switch			No
Suitable for overload relay			No