



Signalling switch ON-OFF, 10W



Powering Business Worldwide™

Part no. **+IZMX-AS1010**
 Catalog No. **124346**

Delivery program

Product range			Accessories
Accessories			Auxiliary contact
Accessories			Standard auxiliary switch for On-Off signaling
			Standard auxiliary switch for On-Off signaling. The basic device already contains two changeover contacts. Two additional changeover contacts possible.
For use with			IZMX40... INX40...
			10 changeover contacts

Technical data

Rated breaking capacity

Inductive load			
250 V AC		A	10
125 V DC		A	0.5
250 V DC		A	0.25

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	70

Technical data ETIM 6.0

Low-voltage industrial components (EG000017) / Auxiliary contact block (EC000041)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Component for low-voltage switching technology / Auxiliary switch block (ecl@ss8.1-27-37-13-02 [AKN342010])			
Number of contacts as change-over contact			10
Number of contacts as normally open contact			0
Number of contacts as normally closed contact			0
Rated operation current I _e at AC-15, 230 V		A	10
Type of electric connection			Flat plug-in connection
Model			Half-integrated
Mounting method			Other