



Fuse-link, low voltage, 15 A, AC 125 V, UL, time-delay

Catalog No. **SL-15**

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	15
Rated voltage			AC 125 V
Description			Rejection base
Breaking Capacity		kA	10
usable for size/applications			fit into SA holder
Release characteristic	class		time-delay
Standard/Approval			UL
Shape			Plastic base with rejection threads
Material			plastic
Standards/Regulations			UL
Optional accessories			fuse-holder SA-15

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ecl@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			Other
Rated current		A	15
Rated voltage		V	125
Voltage type			AC
Rated switching capacity		kA	10
Utilization category			Other
Type of fuse status indicator			None
Insulated metal gripping lugs (IMGL)			No

Additional product information (links)

Product datasheet (pdf)	http://www.cooperindustries.com/content/dam/public/bussmann/Electrical/Resources/product-datasheets-a/Bus_Ele_DS_1033_SL.pdf
-------------------------	---