



**Residual current circuit-breaker, 125A, 4p, 5mA, A-Char**

**Part no.** PFDM-125/4/05-A  
**Catalog No.** 235923

Similar to illustration

**Design verification as per IEC/EN 61439**

Technical data for design verification			
Rated operational current for specified heat dissipation	$I_n$	A	125
Heat dissipation per pole, current-dependent	$P_{vid}$	W	0
Equipment heat dissipation, current-dependent	$P_{vid}$	W	33.6
Static heat dissipation, non-current-dependent	$P_{vs}$	W	0
Heat dissipation capacity	$P_{diss}$	W	0
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	60
Starting at 40 °C, the max. permissible continuous current decreases by 1.8% for every 1 °C			

**Technical data ETIM 7.0**

Circuit breakers and fuses (EG000020) / Residual current circuit breaker (RCCB) (EC000003)			
Electric engineering, automation, process control engineering / Electrical installation, device / Residual current protection system / Residual current circuit breaker (RCCB) (ecl@ss10.0.1-27-14-22-01 [AAB906014])			
Number of poles			4
Rated voltage		V	400
Rated current		A	125
Rated fault current		mA	500
Rated insulation voltage $U_i$		V	400
Rated impulse withstand voltage $U_{imp}$		kV	4
Mounting method			DIN rail
Leakage current type			A
Selective protection			No
Short-time delayed tripping			No
Short-circuit breaking capacity (I <sub>cw</sub> )		kA	10
Surge current capacity		kA	0.2
Frequency			50 Hz
Additional equipment possible			Yes
With interlocking device			Yes
Degree of protection (IP)			IP20
Width in number of modular spacings			4
Built-in depth		mm	71.5
Ambient temperature during operating		°C	-25 - 40
Pollution degree			2
Connectable conductor cross section multi-wired		mm <sup>2</sup>	1.5 - 16
Connectable conductor cross section solid-core		mm <sup>2</sup>	1.5 - 35