



**Motor cable, 5m, halogen free, for RA-SP**

**Part no.** SET-M4/5-HF  
**Article no.** 265622  
**Catalog No.** SET-M4-5-HF

## Delivery programme

Description		Motor cable 5 m, halogen free, 4 x 1.5 mm <sup>2</sup> + 2 x (2 x 0.75) mm <sup>2</sup> , metal plug
<b>For use with</b>		
For use with		RA-SP

## Technical data ETIM 4.0

Nominal cross section conductor	mm <sup>2</sup>	1,5
Conductor category		Class 6 = very flexible
Number of cores		8
Core insulation		-
Core identification		Numbers
Protective conductor		Yes
Screen		Yes
Material outer sheath		-
Colour outer sheath		Orange
Model		Round
Low smoke (acc. EN 61034-2)		No
Halogen free (acc. EN 50267-2-2)		Yes
Flame retardant		-
Oil resistant (acc. EN 60811-2-1)		Yes
Outer diameter approx.	mm	12
Cable width approx.	mm	0
Cable height approx.	mm	0
Max. conductor temperature	°C	70
Operating temperature, flexible	°C	-30 - 70
Operating temperature, fix	°C	-30 - 70
Nominal voltage U <sub>0</sub>	V	300
Nominal voltage U	V	500

## Additional product information (links)

<b>AWA2190-1936 Rapid Link: Speed Control Unit</b>	
	<a href="#">AWA2190-1936 Rapid Link: Speed Control Unit</a>
<b>AWA2190-2054 Motor cable Speed Control Unit</b>	
	<a href="#">AWA2190-2054 Motor cable Speed Control Unit</a>
<b>AWB2190-1430 Rapid Link Switching and Installation System</b>	
	<a href="#">AWB2190-1430 Schalt- und Installationssystem Rapid Link - Deutsch</a>
	<a href="#">AWB2190-1430 Rapid Link Switching and Installation System - English</a>
	<a href="#">AWB2190-1430 Système de commande et d'installation Rapid Link - français</a>