



Fuse-link, LV, 8 A, AC 500 V, 10 x 38 mm, aM, IEC, indicating

Catalog No. C10M8I

Delivery program

Product range			Fuse
Basic function			Fuse-link
Field of application			low voltage
Rated current	I	A	8
Rated voltage			AC 500 V
Size			10 x 38 mm
Utilization category			aM
Status indicator			with indicator
Standard/Approval			IEC
Shape			cylindrical
Standards/Regulations			IEC 60269-2

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Cylindrical fuse (EC002704)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Cylindrical fuse (safety fuse) (ecl@ss10.0.1-27-14-20-02 [AFZ797013])			
Size			10x38 mm
Rated voltage		V	500 - 500
Rated voltage			Other
Voltage type			AC
Utilization category			aM (switchgear protection)
Rated operating frequency		Hz	45 - 62
Nominal current		A	8
With striker			No
Release characteristic			Other
Breaking capacity		kA	120

Assets (links)

Declaration of CE Conformity
00003176

Additional product information (links)

Product datasheet (pdf)	http://www1.cooperbusmann.com/pdf/7eba542b-1b11-4a86-afd0-69ed8f8a374b.pdf
-------------------------	---