

Main switch, P1, 32 A, rear mounting, 3 pole, STOP function, With black rotary handle and locking ring, Lockable in the 0 (Off) position



**Part no. P1-32/V/SVB-SW
055484**

| General specifications | | |
|--|--|--|
| Product name | | Eaton Moeller® series P1 Main switch |
| Part no. | | P1-32/V/SVB-SW |
| EAN | | 4015080554844 |
| Product Length/Depth | | 90 millimetre |
| Product height | | 70 millimetre |
| Product width | | 54 millimetre |
| Product weight | | 0.217 kilogram |
| Certifications | | UL File No.: E36332 UL 60947-4-1 IEC/EN 60947-3 VDE 0660 UL IEC/EN 60204 CSA-C22.2 No. 60947-4-1-14 CSA File No.: 012528 CSA CSA-C22.2 No. 94 IEC/EN 60947 CSA Class No.: 3211-05 UL Category Control No.: NLRV CE UL CSA |
| Product Tradename | | P1 |
| Product Type | | Main switch |
| Product Sub Type | | None |
| Catalog Notes | | Rated Short-time Withstand Current (Icw) for a time of 1 second |
| Features & Functions | | |
| Features | | Version as main switch Version as maintenance-/service switch |
| Fitted with: | | Black rotary handle and locking ring |
| Functions | | Interlockable STOP function |
| Locking facility | | Lockable in the 0 (Off) position |
| Number of poles | | 3 |
| General information | | |
| Accessories | | Auxiliary contact or neutral conductor fitted by user. |
| Degree of protection | | NEMA 1 |
| Degree of protection (front side) | | IP65 |
| Lifespan, mechanical | | 300,000 Operations |
| Mounting method | | Rear mounting |
| Mounting position | | As required |
| Operating frequency | | 1200 Operations/h |
| Overvoltage category | | III |
| Pollution degree | | 3 |
| Rated impulse withstand voltage (Uimp) | | 6000 V AC |
| Safe isolation | | 440 V AC, Between the contacts, According to EN 61140 |
| Safety parameter (EN ISO 13849-1) | | B10d values as per EN ISO 13849-1, table C.1 |
| Shock resistance | | 15 g, Mechanical, According to IEC/EN 60068-2-27, Half-sinusoidal shock 20 ms |
| Suitable for | | Branch circuits, suitable as motor disconnect, (UL/CSA) |
| Climatic environmental conditions | | |
| Ambient operating temperature - min | | -25 °C |
| Ambient operating temperature - max | | 50 °C |

| | |
|--|--|
| Ambient operating temperature (enclosed) - min | -25 °C |
| Ambient operating temperature (enclosed) - max | 40 °C |
| Climatic proofing | Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78 |
| Terminal capacities | |
| Terminal capacity | 14 - 8 AWG, solid or flexible with ferrule 2 x (1 - 4) mm ² , flexible with ferrules to DIN 46228 1 x (1.5 - 6) mm ² , solid or stranded 1 x (1 - 4) mm ² , flexible with ferrules to DIN 46228 2 x (1.5 - 6) mm ² , solid or stranded |
| Screw size | M4, Terminal screw |
| Tightening torque | 1.6 Nm, Screw terminals 14.1 lb-in, Screw terminals |
| Electrical rating | |
| Rated breaking capacity at 220/230 V (cos phi to IEC 60947-3) | 260 A |
| Rated breaking capacity at 400/415 V (cos phi to IEC 60947-3) | 300 A |
| Rated breaking capacity at 500 V (cos phi to IEC 60947-3) | 290 A |
| Rated breaking capacity at 660/690 V (cos phi to IEC 60947-3) | 250 A |
| Rated operational current (Ie) at AC-3, 220 V, 230 V, 240 V | 26.4 A |
| Rated operational current (Ie) at AC-3, 380 V, 400 V, 415 V | 26.4 A |
| Rated operational current (Ie) at AC-3, 500 V | 23.4 A |
| Rated operational current (Ie) at AC-3, 660 V, 690 V | 14.7 A |
| Rated operational current (Ie) at AC-21, 440 V | 32 A |
| Rated operational current (Ie) at AC-23A, 230 V | 32 A |
| Rated operational current (Ie) at AC-23A, 400 V, 415 V | 32 A |
| Rated operational current (Ie) at AC-23A, 500 V | 30 A |
| Rated operational current (Ie) at AC-23A, 690 V | 19.8 A |
| Rated operational current (Ie) at DC-1, load-break switches I/r = 1 ms | 32 A |
| Rated operational current (Ie) at DC-23A, 24 V | 25 A |
| Rated operational current (Ie) at DC-23A, 48 V | 25 A |
| Rated operational current (Ie) at DC-23A, 60 V | 25 A |
| Rated operational current (Ie) at DC-23A, 120 V | 12 A |
| Rated operational power at AC-3, 380/400 V, 50 Hz | 13 kW |
| Rated operational power at AC-3, 415 V, 50 Hz | 13 kW |
| Rated operational power at AC-3, 500 V, 50 Hz | 18.5 kW |
| Rated operational power at AC-3, 690 V, 50 Hz | 15 kW |
| Rated operational power at AC-23A, 220/230 V, 50 Hz | 7.5 kW |
| Rated operational power at AC-23A, 400 V, 50 Hz | 15 kW |
| Rated operational power at AC-23A, 500 V, 50 Hz | 18.5 kW |
| Rated operational power at AC-23A, 690 V, 50 Hz | 15 kW |
| Rated operational voltage (Ue) at AC - max | 690 V |
| Rated uninterrupted current (Iu) | 32 A |
| Uninterrupted current | Rated uninterrupted current Iu is specified for max. cross-section. |
| Short-circuit rating | |
| Rated conditional short-circuit current (Iq) | 80 kA |
| Rated short-time withstand current (Icw) | 640 A, Contacts, 1 second 0.64 kA |
| Short-circuit current rating (basic rating) | 110A, max. Fuse, SCCR (UL/CSA) 5 kA, SCCR (UL/CSA) |
| Short-circuit current rating (high fault) | 50 A, Class J, max. Fuse, SCCR (UL/CSA) 10 kA, SCCR (UL/CSA) |
| Short-circuit protection rating | 50 A gG/gL, Fuse, Contacts |
| Switching capacity | |
| Load rating | 1.3 x I# (with intermittent operation class 12, 60 % duty factor) 1.6 x I# (with intermittent operation class 12, 40 % duty factor) 2 x I# (with intermittent operation class 12, 25 % duty factor) |
| Number of contacts in series at DC-23A, 24 V | 1 |
| Number of contacts in series at DC-23A, 48 V | 2 |
| Number of contacts in series at DC-23A, 60 V | 2 |

| | | |
|--|--|--|
| Number of contacts in series at DC-23A, 120 V | | 3 |
| Switching capacity (main contacts, general use) | | 30 A, Rated uninterrupted current max. (UL/CSA) |
| Switching capacity (auxiliary contacts, general use) | | 10A, IU, (UL/CSA) |
| Switching capacity (auxiliary contacts, pilot duty) | | A600 (UL/CSA) P600 (UL/CSA) |
| Rated making capacity up to 690 V (cos phi to IEC/EN 60947-3) | | 320 A |
| Voltage per contact pair in series | | 60 V |
| Motor rating | | |
| Assigned motor power at 115/120 V, 60 Hz, 1-phase | | 1 HP |
| Assigned motor power at 200/208 V, 60 Hz, 1-phase | | 2 HP |
| Assigned motor power at 200/208 V, 60 Hz, 3-phase | | 3 HP |
| Assigned motor power at 230/240 V, 60 Hz, 1-phase | | 3 HP |
| Assigned motor power at 230/240 V, 60 Hz, 3-phase | | 7.5 HP |
| Assigned motor power at 460/480 V, 60 Hz, 3-phase | | 10 HP |
| Assigned motor power at 575/600 V, 60 Hz, 3-phase | | 15 HP |
| Contacts | | |
| Control circuit reliability | | 1 failure per 100,000 switching operations statistically determined, at 24 V DC, 10 mA) |
| Number of auxiliary contacts (change-over contacts) | | 0 |
| Number of auxiliary contacts (normally closed contacts) | | 0 |
| Number of auxiliary contacts (normally open contacts) | | 0 |
| Actuator | | |
| Actuator color | | Black |
| Actuator type | | Door coupling rotary drive |
| Design verification | | |
| Equipment heat dissipation, current-dependent Pvid | | 0 W |
| Heat dissipation capacity Pdiss | | 0 W |
| Heat dissipation per pole, current-dependent Pvid | | 1.8 W |
| Rated operational current for specified heat dissipation (In) | | 32 A |
| Static heat dissipation, non-current-dependent Pvs | | 0 W |
| 10.2.2 Corrosion resistance | | Meets the product standard's requirements. |
| 10.2.3.1 Verification of thermal stability of enclosures | | Meets the product standard's requirements. |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat | | Meets the product standard's requirements. |
| 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects | | Meets the product standard's requirements. |
| 10.2.4 Resistance to ultra-violet (UV) radiation | | UV resistance only in connection with protective shield. |
| 10.2.5 Lifting | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.6 Mechanical impact | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.7 Inscriptions | | Meets the product standard's requirements. |
| 10.3 Degree of protection of assemblies | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.4 Clearances and creepage distances | | Meets the product standard's requirements. |
| 10.5 Protection against electric shock | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.6 Incorporation of switching devices and components | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.7 Internal electrical circuits and connections | | Is the panel builder's responsibility. |
| 10.8 Connections for external conductors | | Is the panel builder's responsibility. |
| 10.9.2 Power-frequency electric strength | | Is the panel builder's responsibility. |
| 10.9.3 Impulse withstand voltage | | Is the panel builder's responsibility. |
| 10.9.4 Testing of enclosures made of insulating material | | Is the panel builder's responsibility. |
| 10.10 Temperature rise | | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.12 Electromagnetic compatibility | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.13 Mechanical function | | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |

Technical data ETIM 9.0

| Low-voltage industrial components (EG000017) / Switch disconnecter (low voltage) (EC000216) | | | |
|--|--|----|--|
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Switch disconnecter (ec@ss13-27-37-14-03 [AKF060018]) | | | |
| Version as main switch | | | Yes |
| Version as maintenance-/service switch | | | Yes |
| Version as safety switch | | | No |
| Version as emergency stop installation | | | No |
| Version as reversing switch | | | No |
| Number of switches | | | 1 |
| Max. rated operation voltage Ue AC | | V | 690 |
| Rated operating voltage | | V | 690 - 690 |
| Rated permanent current Iu | | A | 32 |
| Rated permanent current at AC-23, 400 V | | A | 32 |
| Rated permanent current at AC-21, 400 V | | A | 32 |
| Rated operation power at AC-3, 400 V | | kW | 13 |
| Rated short-time withstand current Icw | | kA | 0.64 |
| Rated operation power at AC-23, 400 V | | kW | 15 |
| Switching power at 400 V | | kW | 15 |
| Conditioned rated short-circuit current Iq | | kA | 80 |
| Number of poles | | | 3 |
| Number of auxiliary contacts as normally closed contact | | | 0 |
| Number of auxiliary contacts as normally open contact | | | 0 |
| Number of auxiliary contacts as change-over contact | | | 0 |
| Motor drive optional | | | No |
| Motor drive integrated | | | No |
| Voltage release optional | | | No |
| Device construction | | | Built-in device fixed built-in technique |
| Suitable for floor mounting | | | No |
| Suitable for front mounting 4-hole | | | No |
| Suitable for front mounting centre | | | No |
| Suitable for distribution board installation | | | No |
| Suitable for intermediate mounting | | | No |
| Colour control element | | | Black |
| Type of control element | | | Door coupling rotary drive |
| Interlockable | | | Yes |
| Type of electrical connection of main circuit | | | Screw connection |
| With pre-assembled cabling | | | No |
| Degree of protection (IP), front side | | | IP65 |
| Degree of protection (NEMA) | | | 1 |
| Width | | mm | 54 |
| Height | | mm | 70 |
| Depth | | mm | 90 |
| Width in number of modular spacings | | | |