

Selector switch, 3 positions, white, maintained

Part no. **Q18WK3R**
072309

General specifications	
Product name	Eaton Moeller® series RMQ16 Changeover switch
Part no.	Q18WK3R
EAN	4015080723097
Product Length/Depth	65 millimetre
Product height	18 millimetre
Product width	18 millimetre
Product weight	0.012 kilogram
Certifications	CSA File No.: 46552 CE CSA Class No.: 3211-03 UL 508 UL UL File No.: E29184 UL Category Control No.: NKCR IEC/EN 60947 CSA-C22.2 No. 14-05 CSA IEC/EN 60947-5
Product Tradename	RMQ16
Product Type	Changeover switch
Product Sub Type	None
Catalog Notes	Use of insulated ferrule ISH 2,8 > 24 V AC/DC recommended Use of insulated ferrule ISH 2,8 > 50 V AC or 120 V DC is mandatory, even on unused blade terminals
Features & Functions	
Bezel color	Black
Bezel material	Plastic
Design	With thumb-grip
Fitted with:	Front ring VS anti-rotation tab
General information	
Degree of protection	NEMA 1
Degree of protection (front side)	IP65
Lifespan, mechanical	3,000,000 Operations
Opening diameter	16 mm
Operating frequency	1800 Operations/h
Operating torque	0.2 N·m
Overvoltage category	III
Pollution degree	3
Product category	RMQ16
Size	Front dimensions: 18 x 18 mm
Rated impulse withstand voltage (Uimp)	800 V AC
Switching angle	45 °
Terminal capacity	0.5 - 1.0 mm ²
Terminal size	2.8 x 0.8 mm to DIN 46247 and IEC 60760, Fast-on connectors 2.8 x 0.8 mm to DIN 46244, Blade terminal
Type	Selector switch actuator
Ambient conditions, mechanical	
Mounting position	As required
Shock resistance	40 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Mechanical, According to IEC/EN 60068-2-27
Climatic environmental conditions	
Ambient operating temperature - min	-25 °C

Ambient operating temperature - max		60 °C
Ambient operating temperature (enclosed) - min		-25 °C
Ambient operating temperature (enclosed) - max		40 °C
Climatic proofing		Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
Electrical rating		
Rated insulation voltage (Ui)		250 V
Rated operational voltage (Ue) at AC - max		24 V
Actuator		
Actuator color		White
Actuator function		Switching function latching Maintained
Actuator type		Toggle
Number of switch positions		3
Contacts		
Control circuit reliability		1 failure per 10,000,000 switching operations (Statistically determined, at 24 V DC/5 mA) 1 failure per 5,000,000 switching operations (statistically determined, at 5 V DC/1 mA)
Communication		
Connection to SmartWire-DT		No
Design verification		
Equipment heat dissipation, current-dependent Pvid		0 W
Heat dissipation capacity Pdis		0 W
Heat dissipation per pole, current-dependent Pvid		0 W
Rated operational current for specified heat dissipation (In)		0 A
Static heat dissipation, non-current-dependent Pvs		0 W
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Please enquire
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		Not applicable.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Front element for selector switch (EC000222)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Front element for selector switches (ecl@ss13-27-37-12-13 [AKF031019])		
Number of switch positions		3
Type of control element		Toggle

Suitable for illumination		No
Colour control element		White
Colour indicator light cap		Other
Construction type lens		Square
Hole diameter	mm	16
Width opening	mm	0
Height opening	mm	0
Switching function latching		Yes
Spring-return		No
With front ring		Yes
Material front ring		Plastic
Colour front ring		Black
Degree of protection (IP), front side		IP65
Degree of protection (NEMA)		1