

## Emergency-stop pushbutton, red, maintained

**Part no.**                    **Q25PV**  
**072370**

<b>General specifications</b>	
Product name	Eaton Moeller® series RMQ16 Emergency stop/emergency switching off pushbutton
Part no.	Q25PV
EAN	4015080723707
Product Length/Depth	85 millimetre
Product height	28 millimetre
Product width	28 millimetre
Product weight	0.024 kilogram
Certifications	UL UL 508 CE IEC/EN 60947-5 UL Category Control No.: NKCR CSA File No.: 46552 IEC/EN 60947 UL File No.: E29184 CSA Class No.: 3211-03 CSA CSA-C22.2 No. 14-05
Product Tradename	RMQ16
Product Type	Emergency stop/emergency switching off pushbutton
Product Sub Type	None
Catalog Notes	Pushbutton remains in pushed position Use of insulated ferrule ISH 2,8 > 24 V AC/DC recommended Use of insulated ferrule ISH 2,8 > 50 V AC or 120 V DC is mandatory, even on unused blade terminals
<b>Features &amp; Functions</b>	
Bezel color	Other
Bezel material	Other
Design	Mushroom-shaped
Features	Tamper-proof (according to ISO 13850, EN 418)
Illumination	Non-illuminated
Unlocking method	Pull-release
<b>General information</b>	
Degree of protection	IP65 NEMA 1
Lifespan, mechanical	100,000 Operations
Opening diameter	16 mm
Operating frequency	600 Operations/h
Overvoltage category	III
Pollution degree	3
Product category	RMQ16
Size	Front dimensions: 25 × 25 mm
Rated impulse withstand voltage (Uimp)	800 V AC
Suitable for	Emergency stop
Terminal capacity	0.5 - 1.0 mm <sup>2</sup>
Terminal size	2.8 x 0.8 mm to DIN 46247 and IEC 60760, Fast-on connectors 2.8 x 0.8 mm to DIN 46244, Blade terminal
Type	Controlled stop pushbutton/emergency-stop button
<b>Ambient conditions, mechanical</b>	
Mounting position	As required
Shock resistance	Mechanical, According to IEC/EN 60068-2-27 40 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms
<b>Climatic environmental conditions</b>	

Ambient operating temperature - min		-25 °C
Ambient operating temperature - max		60 °C
Ambient operating temperature (enclosed) - min		25 °C
Ambient operating temperature (enclosed) - max		40 °C
Climatic proofing		Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-78
<b>Electrical rating</b>		
Rated insulation voltage (Ui)		250 V
Rated operational voltage (Ue) at AC - max		24 V
<b>Actuator</b>		
Actuating force		25 N
Actuator color		Red
Actuator diameter		28 mm
Actuator function		Pull-to-release Switching function latching
<b>Contacts</b>		
Control circuit reliability		1 failure per 10,000,000 switching operations (Statistically determined, at 24 V DC/5 mA) 1 failure per 5,000,000 switching operations (statistically determined, at 5 V DC/1 mA)
<b>Communication</b>		
Connection to SmartWire-DT		No
<b>Design verification</b>		
Equipment heat dissipation, current-dependent Pvid		0 W
Heat dissipation capacity Pdiss		0 W
Heat dissipation per pole, current-dependent Pvid		0 W
Rated operational current for specified heat dissipation (In)		0 A
Static heat dissipation, non-current-dependent Pvs		0 W
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Please enquire
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		Not applicable.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Front element for mushroom push-button (EC001038)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Front element for mushroom push-button actuators (ec1@ss13-27-37-12-12 [AKF030019])		
Colour button		Red

Construction type lens		Round
Diameter cap	mm	28
Hole diameter	mm	16
Width opening	mm	0
Height opening	mm	0
Degree of protection (IP)		IP65
Degree of protection (NEMA)		1
Type of button		High
Suitable for illumination		No
With lighting		No
Supply voltage lamp	V	0
Switching function latching		Yes
Spring-return		No
With front ring		No
Material front ring		Other
Colour front ring		Other
Suitable for emergency stop		Yes
Unlocking method		Pull-release