

Copper strip, tinned, 200A, 9x9x0.8mm, black

Part no. **CU-BAND9X9X0,8-BK**
081515

General specifications		
Product name		Eaton xEffect Multi-Layer Copper Band Enclosures Switch- & Controlgear Enclosure
Part no.		CU-BAND9X9X0,8-BK
EAN		4015080815150
Product Length/Depth		2000 millimetre
Product height		9 millimetre
Product width		12 millimetre
Product weight		1.311 kilogram
Compliances		EN 60439-1 CE marking UL 758 UL CSA09 (max. 105 °C) EN 60439-3 RoHS conform
Certifications		North America (UL listed, certified by UL for use in Canada) UL (Category Control Number AVL2) UL (File No. E248096)
Product Tradename		xEffect Multi-Layer Copper Band
Product Type		Enclosures
Product Sub Type		Switch- & Controlgear Enclosure
Delivery program		
Type		General switchboard accessory
Accessory/spare part type		Copper band insulated
Color		Black, similar to RAL 9005
Amperage rating		200 A
Technical Data - Electrical		
Voltage rating		1000 V AC, 1500 V DC
Voltage rating (UL CSA 13)		Max. 600 V AC, 750 V DC
Rated operation current (Ie)		200 A
Dielectric strength		20 kV/mm
Technical Data - Mechanical		
Cross section		64.8 mm ²
Number of fuse holders (knife blade)		9
Busbar thickness		11.2 mm
Dimensions - band specification		9 mm x 9 mm x 0.8 mm
Lamella thickness		0.8 mm
Additional information		
Features		Self-extinguishing acc. UL 94 V0 Laminated
Special features		E-Cu laminated conductor, tin-plated UL approved up to max. 600 V AC Insulating material heat resistant up to +105 °C
Used with		Copper band isolated Appliance wiring material

Technical data ETIM 9.0

Energy distribution systems (EG000015) / Wiring band (EC001898)		
Electric engineering, automation, process control engineering / Electrical insulation and connecting material / Energy distribution system / Wiring band (ecl@ss13-27-40-06-12 [AC0387016])		
Rated operation current	A	200
Length	mm	2000
Width	mm	12
Thickness	mm	11.2

Laminated		Yes
Lamella thickness	mm	0.8
Number of lamellas		9