

Molded Case Switch, 3p, 125A



Part no. NS1-125-NA
102683
EL Number 4315507
(Norway)

General specifications		
Product name		Eaton Moeller series NZM molded case switch
Part no.		NS1-125-NA
EAN		4015081025435
Product Length/Depth		88 millimetre
Product height		145 millimetre
Product width		90 millimetre
Product weight		1.046 kilogram
Compliances		RoHS conform
Certifications		UL (File No. E148671) CSA (Class No. 4652-06) UL 489 CE marking CSA-C22.2 No. 5-09 UL (Category Control Number WJAZ) CSA (File No. 22086) Specially designed for North America IEC UL/CSA CSA certified UL listed IEC 60947-2
Product Tradename		NZM
Product Type		Molded case switch
Product Sub Type		None
Delivery program		
Application		Branch circuits, feeder circuits
Type		Switch-disconnector
Circuit breaker frame type		N1
Number of poles		Three-pole
Amperage Rating		125 A
Features		Protection unit
Special features		IEC/EN 60947-2: circuit breakers without overcurrent (CBI-X) with main switch characteristics and isolating characteristics to IEC/EN 60204. Rated current = rated uninterrupted current: 125 A Terminal capacity hint: Up to 95 mm ² can be connected depending on the cable manufacturer.
Technical Data - Electrical		
Voltage rating		690 V - 690 V
Rated operating voltage Ue (UL) - max		480 Y / 277 V
Rated insulation voltage (Ui)		690 V AC
Rated impulse withstand voltage (Uimp) at auxiliary contacts		6000 V
Rated impulse withstand voltage (Uimp) at main contacts		6000 V
Current rating (Iu) (UL 489 csa 22.2 no. 5.1)		125 A
Rated current (Iu)		125 A
Instantaneous current setting (Ii) - min		1250 A
Instantaneous current setting (Ii) - max		1250 A
Overload current setting (Ir) - min		0 A
Overload current setting (Ir) - max		0 A
Short delay current setting (I _{sd}) - min		0 A
Short delay current setting (I _{sd}) - max		0 A
Short-circuit release non-delayed setting - min		1250 A
Short-circuit release non-delayed setting - max		1250 A
Rated short-circuit breaking capacity I _{cs} (IEC/EN 60947) at 230 V, 50/60 Hz		85 kA

Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 400/415 V, 50/60 Hz		50 kA
Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 440 V, 50/60 Hz		35 kA
Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 525 V, 50/60 Hz		10 kA
Rated short-circuit breaking capacity Ics (IEC/EN 60947) at 690 V, 50/60 Hz		7.5 kA
Rated short-circuit making capacity Icm at 240 V, 50/60 Hz		187 kA
Rated short-circuit making capacity Icm at 400/415 V, 50/60 Hz		105 kA
Rated short-circuit making capacity Icm at 440 V, 50/60 Hz		74 kA
Rated short-circuit making capacity Icm at 525 V, 50/60 Hz		53 kA
Rated short-circuit making capacity Icm at 690 V, 50/60 Hz		17 kA
Short-circuit total breaktime		< 10 ms
Electrical connection type of main circuit		Frame clamp
Number of operations per hour - max		120
Handle type		Rocker lever
Overvoltage category		III
Pollution degree		3
Lifespan, electrical		10000 operations at 400 V AC-1 10000 operations at 415 V AC-1 7500 operations at 690 V AC-1
Direction of incoming supply		As required
Technical Data - Mechanical		
Mounting Method		DIN rail (top hat rail) mounting optional Built-in device fixed built-in technique Fixed
Degree of protection		IP20 In the area of the HMI devices: IP20 (basic protection type)
Degree of protection (IP), front side		IP66 (with door coupling rotary handle) IP40 (with insulating surround)
Degree of protection (terminations)		IP10 (tunnel terminal) IP00 (terminations, phase isolator and band terminal)
Number of auxiliary contacts (change-over contacts)		0
Number of auxiliary contacts (normally closed contacts)		0
Number of auxiliary contacts (normally open contacts)		0
Position of connection for main current circuit		Front side
Switch positions		I, +, 0
Special features		IEC/EN 60947-2: circuit breakers without overcurrent (CBI-X) with main switch characteristics and isolating characteristics to IEC/EN 60204. Rated current = rated uninterrupted current: 125 A Terminal capacity hint: Up to 95 mm ² can be connected depending on the cable manufacturer.
Lifespan, mechanical		20000 operations
Technical Data - Mechanical - Terminals		
Standard terminals		Box terminal
Optional terminals		Connection on rear. Screw terminal. Tunnel terminal
Terminal capacity (aluminum solid conductor/cable)		10 mm ² - 16 mm ² (1x) direct at switch rear-side connection 10 mm ² - 16 mm ² (2x) direct at switch rear-side connection 16 mm ² (1x) at tunnel terminal
Terminal capacity (aluminum stranded conductor/cable)		25 mm ² - 35 mm ² (2x) direct at switch rear-side connection 25 mm ² - 95 mm ² (1x) at 1-hole tunnel terminal 25 mm ² - 35 mm ² (1x) direct at switch rear-side connection
Terminal capacity (copper busbar)		Min. 12 mm x 5 mm direct at switch rear-side connection M6 at rear-side screw connection NA: M6 at rear-side screw connection NA: max. 16 mm x 5 mm direct at switch rear-side connection NA: min. 12 mm x 5 mm direct at switch rear-side connection Max. 16 mm x 5 mm direct at switch rear-side connection
Terminal capacity (copper solid conductor/cable)		10 mm ² - 16 mm ² (1x) direct at switch rear-side connection 6 mm ² - 16 mm ² (2x) at box terminal 6 mm ² - 16 mm ² (2x) direct at switch rear-side connection 10 mm ² - 16 mm ² (1x) at box terminal NA: 12 - 6 AWG (1x) direct at switch rear-side connection NA: 12 - 6 AWG (1x) at box terminal NA: 9 - 6 AWG (2x) direct at switch rear-side connection 16 mm ² (1x) at tunnel terminal NA: 6 AWG (1x) at tunnel terminal
Terminal capacity (copper stranded conductor/cable)		25 mm ² (2x) direct at switch rear-side connection NA: 4 - 2/0 AWG/kcmil (1x) at box terminal 25 mm ² - 70 mm ² (1x) direct at switch rear-side connection 6 mm ² - 25 mm ² (2x) at box terminal

		25 mm ² - 95 mm ² (1x) at 1-hole tunnel terminal 10 mm ² - 70 mm ² (1x) at box terminal NA: 4 - 3/0 AWG/kcmil (1x) at 1-hole tunnel terminal
Terminal capacity (copper strip)		Min. 2 segments of 9 mm x 0.8 mm at box terminal Max. 9 segments of 9 mm x 0.8 mm at box terminal
Design verification as per IEC/EN 61439 - technical data		
Rated operational current for specified heat dissipation (In)		125 A
Equipment heat dissipation, current-dependent		26.34 W
Ambient operating temperature - min		-25 °C
Ambient operating temperature - max		70 °C
Ambient storage temperature - min		40 °C
Ambient storage temperature - max		70 °C
Design verification as per IEC/EN 61439		
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.
Additional information		
Functions		Disconnectors/main switches

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Power circuit-breaker for trafo/generator/installation protection (EC000228)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Circuit breaker for power transformer, generator and system protection (ecl@ss13-27-37-04-09 [AJZ716018])			
Rated permanent current I _u	A	125	
Rated voltage	V	690 - 690	
Rated short-circuit breaking capacity I _{cu} at 400 V, 50 Hz	kA	50	
Overload release current setting	A	0 - 0	
Adjustment range short-term delayed short-circuit release	A	0 - 0	
Adjustment range undelayed short-circuit release	A	1250 - 1250	
Power loss	W	26.3	
Device construction		Built-in device fixed built-in technique	
Integrated earth fault protection		No	
Type of electrical connection of main circuit		Frame clamp	
Suitable for DIN rail (top hat rail) mounting		No	
DIN rail (top hat rail) mounting optional		Yes	
Number of auxiliary contacts as normally closed contact		0	

Number of auxiliary contacts as normally open contact			0
Number of auxiliary contacts as change-over contact			0
With switched-off indicator			No
With integrated under voltage release			No
Number of poles			3
Position of connection for main current circuit			Front side
Type of control element			Rocker lever
Complete device with protection unit			Yes
Motor drive integrated			No
Motor drive optional			No
Degree of protection (IP)			IP20