

Profile busbar, T, cu, 1140mm², tinned, 2.40 m



Part no. **CU-BAR-1140/T**
107168

General specifications		
Product name		Eaton xEffect SASY 60i copper busbar profiled
Part no.		CU-BAR-1140/T
EAN		4015081069316
Product Length/Depth		2400 millimetre
Product height		70 millimetre
Product width		30 millimetre
Product weight		24.36 kilogram
Compliances		RoHS conform
Certifications		EN 13061 UL 508
Product Tradename		xEffect SASY 60i
Product Type		Copper busbar
Product Sub Type		Profiled
Delivery program		
Type		185 mm system System for profile busbar
Model		Profile
Nominal current		2500 A
Technical Data - Electrical		
Rated uninterrupted current (I _u) of conductor		2500 A (1140 mm ² , T _u =35 °C and T _s =65 °C)
Rated operation current (I _e)		2500 A
Technical Data - Mechanical		
Surface protection		Tinned
Cross section		1140 mm ²
Material		Copper, tinned
Additional information		
Functions		E-CU triple T profiled busbar System for profile busbars Profiled busbar
Used with		For carrier BBS-3/FL-185, KSX-3.... System for profile busbar 185 mm system

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Busbar (EC001522)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Busbar trunking system (LV circuitry) / Busbar (low-voltage switching technology) (ec1@ss13-27-37-03-03 [ACN949016])			
Rated current I _n		A	2500
Model			Profile
Length		mm	2400
Width		mm	30
Height		mm	70
Flexible			No
Surface protection			Tinned