

Main switch assembly kit, +additional handle, size 2, NA type



Part no. **NZM2-XHB-DA-NA**
116897

General specifications		
Product name		Eaton Moeller series NZM operating element NA
Part no.		NZM2-XHB-DA-NA
EAN		4015081166374
Product Length/Depth		100 millimetre
Product height		432 millimetre
Product width		105 millimetre
Product weight		0.806 kilogram
Compliances		IEC UL/CSA RoHS conform
Certifications		CSA (File No. 22086) UL (File No. E140305) CSA certified CSA (Class No. 1437-01) UL508A UL listed CSA-C22.2 No. 5-09 Specially designed for North America UL (Category Control Number DIHS) NFPA79 IEC60947 CE marking UL489
Product Tradename		NZM
Product Type		Accessories
Product Sub Type		Operating element NA
Delivery program		
Type		Accessory Main switch assembly kit
Features		With black door coupling rotary handle Lockable
Special features		External warning plate/designation label can be clipped on. For enhanced busbar tag shroud on the incomer side, please order IP2X protection against contact with a finger. Kit for use as a main switch
Frame		NZM2
Fitted with:		Add-on rotary handle on switch with "Deliberate Action" operation as per NFPA79 and UL508A Part 2 Black and yellow lightning symbol External warning plate/markings plate in German/English Door coupling rotary handle with rotary drive Padlock Extension shaft NZM...-XV6 for mounting depth 600 mm
Suitable for		Switch disconnecter Power circuit breaker
Used with		N(S)2(-4) PN2(-4) NZM2(-4)
Technical Data - Mechanical		
Color		Black
Cover/door type		Door interlock can be modified such that it can be defeated from the outside using a screwdriver Door interlock not defeated in the locked OFF position. With activated door interlock. Cannot be opened in ON, OFF, or TRIP. Can only be opened in RESET. Door interlock on OFF with max. 3 padlocks
Degree of protection / NEMA enclosure type		IP66 4X. 12
Locking facility		With door interlock Lockable on the switch in the 0 position Lockable on the 0 position on the handle using up to 3 padlocks Can also be modified in I position
Special features		External warning plate/designation label can be clipped on. For enhanced busbar tag shroud on the incomer side, please order IP2X protection against contact with a finger. Kit for use as a main switch

Design verification as per IEC/EN 61439		
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Meets the product standard's requirements.
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Handle for power circuit breaker (EC000229)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Handle for switch devices (ecl@ss13-27-37-04-14 [AKF012019])		
With restart blockage		No
With key lock		No
Padlock locking		Yes
Colour		Black
Suitable for emergency stop		No
With extension shaft		No
Suitable for power circuit breaker		Yes
Suitable for switch disconnecter		Yes
Degree of protection (NEMA)		4X, 12