

## Indicator light, Flat, Screw connection, Lens Without lens, LED green, 230 V AC

**Part no.**                    **C22-L-XG-230**  
**121651**

<b>General specifications</b>		
Product name		Eaton Moeller® series C22 Indicator light
Part no.		C22-L-XG-230
EAN		4015081194650
Product Length/Depth		56 millimetre
Product height		30 millimetre
Product width		30 millimetre
Product weight		0.015 kilogram
Certifications		UL File No.: E29184 CSA-C22.2 No. 14-05 and 94-M91 UL 508 CSA certified VDE 0660 CE marking CSA File No.: 165628 CSA Class No.: 321103 UL Listed IEC/EN 60947-5-1 UL Category Control No.: NKCR
Product Tradename		C22
Product Type		Indicator light
Product Sub Type		None
Catalog Notes		Lenses for indicator lights → accessories
<b>Features &amp; Functions</b>		
Bezel color		Other
Bezel material		Plastic
Design		Flat
Electric connection type		Screw connection
Fitted with:		Front ring Light source
Lens color		Without hood
Light color		Green
<b>General information</b>		
Connection to SmartWire-DT		No
Degree of protection		NEMA 4X, 13 IP67/IP69K
Mounting position		As required
Opening diameter		22.5 mm
Overvoltage category		III
Pollution degree		3
Rated impulse withstand voltage (Uimp)		4000 V AC
Terminal capacity		2 x (0.5 - 1.5) mm <sup>2</sup> , flexible with ferrules to DIN 46228 2 x (0.5 - 1.5) mm <sup>2</sup> , solid
Tightening torque		0.8 Nm, Screw terminals
Type		Indicator lights
Voltage type		AC
<b>Climatic environmental conditions</b>		
Ambient operating temperature - min		-25 °C
Ambient operating temperature - max		70 °C
Climatic proofing		Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
<b>Electrical rating</b>		
Rated conditional short-circuit current (I <sub>q</sub> )		1 kA

Rated insulation voltage (Ui)		250 V
Rated operational voltage (Ue) - min		230 V
Rated operational voltage (Ue) - max		230 V

## Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Indicator light complete (EC000272)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Indicator light complete (ecl@ss13-27-37-12-23 [AKF041019])		
Number of indicator lights		1
Colour lens		Without hood
Type of lamp socket		LED
With light source		Yes
Rated operating voltage Ue	V	230 - 230
Voltage type		AC
Type of electric connection		Screw connection
Construction type lens		Round
Type of lens		Flat
Hole diameter	mm	22.5
Width opening	mm	0
Height opening	mm	0
With front ring		Yes
Material front ring		Plastic
Colour front ring		Other
Degree of protection (IP)		IP67/IP69K
Degree of protection (NEMA)		4X, 13