

Trip block, 1 - 4 A, Motor protection, Connection to SmartWire-DT: no, For use with: PKE12 basic device, PKE32 basic device



Powering Business Worldwide™

Part no. PKE-XTU-4
121724
EL Number 4355186
(Norway)

| General specifications | |
|--|---|
| Product name | Eaton Moeller® series PKE Trip block |
| Part no. | PKE-XTU-4 |
| EAN | 4015081195343 |
| Product Length/Depth | 41.6 millimetre |
| Product height | 64.2 millimetre |
| Product width | 45 millimetre |
| Product weight | 0.086 kilogram |
| Compliances | CE Marked |
| Certifications | UL 508 EN 60947-4-1 CSA Std. C22.2 No. 14-10 IEC 60947-4-1 VDE UL Category Control No.: NLRV CE CSA-C22.2 No. 14-10 VDE 0660 UL IEC/EN 60947 UL File No.: E36332 CSA CSA File No.: 165628 IEC/EN 60947-4-1 CSA Class No.: 3211-05 |
| Product Tradename | PKE |
| Product Type | Accessory |
| Product Sub Type | Trip block |
| Catalog Notes | Also suitable for motors with efficiency class IE3. IE3-ready devices are identified by the logo on their packaging. |
| Features & Functions | |
| Features | Phase-failure sensitivity (according to IEC/EN 60947-4-1, VDE 0660 Part 102) |
| Functions | Motor protection Overload release Motor protection for heavy starting duty |
| Number of poles | Three-pole |
| General information | |
| Current flow times - min | For all combinations with an SWD activation, you need not adhere to the minimum current flow times and minimum cut-out periods. Note: Going below the minimum current flow time can cause overheating of the load (motor). 1000 (Class 20) AC-4 cycle operation, Main conducting paths 700 (Class 10) AC-4 cycle operation, Main conducting paths 900 (Class 15) AC-4 cycle operation, Main conducting paths 500 (Class 5) AC-4 cycle operation, Main conducting paths |
| Cut-out periods - min | ≤ 500 ms, main conducting paths, AC-4 cycle operation |
| Degree of protection | Device: IP20 Terminals: IP00 |
| Operating frequency | 60 Operations/h |
| Overload release current setting - min | 1 A |
| Overload release current setting - max | 4 A |
| Overvoltage category | III |
| Pollution degree | 3 |
| Product category | Accessories |
| Protection | Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274) |
| Rated impulse withstand voltage (Uimp) | 6000 V AC |
| Temperature compensation | -5 - 40 °C to IEC/EN 60947, VDE 0660 |

| | | |
|--|--|--|
| | | -25 - 55 °C, Operating range |
| Used with | | PKE12 and PKE32 basic devices |
| Voltage type | | Self powered |
| Ambient conditions, mechanical | | |
| Shock resistance | | 25 g, Mechanical, according to IEC/EN 60068-2-27, Half-sinusoidal shock 10 ms |
| Climatic environmental conditions | | |
| Altitude | | Max. 2000 m |
| Ambient operating temperature - min | | -25 °C |
| Ambient operating temperature - max | | 55 °C |
| Ambient operating temperature (enclosed) - min | | 25 °C |
| Ambient operating temperature (enclosed) - max | | 40 °C |
| Ambient storage temperature - min | | 40 °C |
| Ambient storage temperature - max | | 80 °C |
| Climatic proofing | | Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30 |
| Electrical rating | | |
| Rated frequency - min | | 50 Hz |
| Rated frequency - max | | 60 Hz |
| Rated operational current (Ie) | | 4 A |
| Rated operational voltage (Ue) at AC - max | | 690 V |
| Rated uninterrupted current (Iu) | | 4 A |
| Short-circuit rating | | |
| Short-circuit release | | Delayed approx. 60 ms, Trip blocks Trip block fixed 15.5 x I _r ± 20% tolerance, Trip blocks |
| Switching capacity | | |
| Switching capacity at AC-3 (up to 690 V) | | 4 A |
| Magnet system | | |
| Rated control supply voltage (Us) at AC, 50 Hz - min | | 0 V |
| Rated control supply voltage (Us) at AC, 50 Hz - max | | 0 V |
| Rated control supply voltage (Us) at AC, 60 Hz - min | | 0 V |
| Rated control supply voltage (Us) at AC, 60 Hz - max | | 0 V |
| Rated control supply voltage (Us) at DC - min | | 0 V |
| Rated control supply voltage (Us) at DC - max | | 0 V |
| Communication | | |
| Connection to SmartWire-DT | | No |
| Design verification | | |
| Equipment heat dissipation, current-dependent P _{vid} | | 0.6 W |
| Heat dissipation capacity P _{diss} | | 0 W |
| Heat dissipation per pole, current-dependent P _{vid} | | 0.2 W |
| Rated operational current for specified heat dissipation (I _n) | | 4 A |
| Static heat dissipation, non-current-dependent P _{vs} | | 0 W |
| 10.2.2 Corrosion resistance | | Meets the product standard's requirements. |
| 10.2.3.1 Verification of thermal stability of enclosures | | Meets the product standard's requirements. |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat | | Meets the product standard's requirements. |
| 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects | | Meets the product standard's requirements. |
| 10.2.4 Resistance to ultra-violet (UV) radiation | | Meets the product standard's requirements. |
| 10.2.5 Lifting | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.6 Mechanical impact | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.7 Inscriptions | | Meets the product standard's requirements. |
| 10.3 Degree of protection of assemblies | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.4 Clearances and creepage distances | | Meets the product standard's requirements. |
| 10.5 Protection against electric shock | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.6 Incorporation of switching devices and components | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.7 Internal electrical circuits and connections | | Is the panel builder's responsibility. |

| | | |
|--|--|--|
| 10.8 Connections for external conductors | | Is the panel builder's responsibility. |
| 10.9.2 Power-frequency electric strength | | Is the panel builder's responsibility. |
| 10.9.3 Impulse withstand voltage | | Is the panel builder's responsibility. |
| 10.9.4 Testing of enclosures made of insulating material | | Is the panel builder's responsibility. |
| 10.10 Temperature rise | | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.12 Electromagnetic compatibility | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.13 Mechanical function | | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |

Technical data ETIM 9.0

| | | | |
|---|--|----|--------------------|
| Low-voltage industrial components (EG000017) / Trip block for power circuit-breaker (EC000617) | | | |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Circuit breaker (LV < 1 kV) / Releasing block for circuit breakers (ec1@ss13-27-37-04-10 [AKF008018]) | | | |
| Type of motor protection | | | Electronic release |
| Number of poles | | | 3 |
| Rated permanent current I _u | | A | 4 |
| Rated switch current | | A | |
| Overload release current setting | | A | 1 - 4 |
| Short-circuit release function | | | Delayed |
| Current setting delayed short-circuit release | | A | |
| Current setting undelayed short-circuit release | | A | |
| With ground fault protection function | | | No |
| External power supply required | | | No |
| Voltage type (supply voltage) | | | |
| Supply voltage AC 50 Hz | | V | |
| Supply voltage AC 60 Hz | | V | |
| Supply voltage DC | | V | |
| Number of auxiliary contacts as normally closed contact | | | |
| Number of auxiliary contacts as normally open contact | | | |
| Number of auxiliary contacts as change-over contact | | | |
| Voltage type (operating voltage) | | | |
| Operating voltage AC 50 Hz | | V | |
| Operating voltage AC 60 Hz | | V | |
| Operating voltage DC | | V | |
| Width | | mm | 45 |
| Height | | mm | 64.2 |
| Depth | | mm | 41.6 |