



Fuse-link, low voltage, 125 A, AC 400 V, 80 kA, NH00, gFF, IEC, dual indicator, insulated gripping lugs

Part no. **125Amp 400V AC GFF 00 NH FUSE**
 Catalog No. **125NHFF00BI-400**

Delivery program

Product range			Fuse
Field of application			low voltage
Rated current	I	A	125
Rated voltage			AC 400 V
Construction size			NH00
Utilization category			gFF
Status indicator			dual indicator
Description			insulated gripping lugs
Breaking Capacity		kA	80
Standard/Approval			IEC
Shape			square-body with knife blade contacts
Standards/Regulations			IEC 60269-1
Optional accessories			fuse-holder SD00-D and SD00-S

Design verification as per IEC/EN 61439

Technical data for design verification			
Rated operational current for specified heat dissipation	I_n	A	125
Equipment heat dissipation, current-dependent	P_{vid}	W	11

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Low Voltage HRC fuse (EC000055)			
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Low-Voltage HRC fuse (ec1@ss10.0.1-27-14-20-05 [AFZ800015])			
Construction size			NH00
Rated current		A	125
Rated voltage		V	400
Voltage type			
Rated switching capacity		kA	120
Utilization category			Other
Type of fuse status indicator			Combination fuse status indicator
Insulated metal gripping lugs (IMGL)			No