




**Fuse switch-disconnector, 3 pole, rear mounting, 800 A, NH3**
**Part no. QSA800-3/3**  
**Catalog No. 1318543**

## Delivery program

Product range			Fuse-switch-disconnector Main switch maintenance switch																												
Part group reference			QSA																												
Stop Function			optional																												
<b>Notes</b>			Suitable for DIN fuse-links (blade contacts type)																												
Information about equipment supplied			Auxiliary contact or neutral conductor fitted by user.																												
Number of poles			3 pole																												
<b>Auxiliary contacts</b>																															
		N/O	0																												
		N/C	0																												
Degree of Protection			IP00 IP20 with terminal cover																												
Design			rear mounting																												
																															
Contact sequence			 <table border="1"> <tr> <td></td><td></td><td></td><td></td> </tr> <tr> <td>L1</td><td>L2</td><td>L3</td><td></td> </tr> <tr> <td>1</td><td>3</td><td>5</td><td></td> </tr> <tr> <td>2</td><td>4</td><td>6</td><td></td> </tr> <tr> <td>T1</td><td>T2</td><td>T3</td><td></td> </tr> <tr> <td>I</td><td></td><td></td><td></td> </tr> <tr> <td>0</td><td></td><td></td><td></td> </tr> </table>					L1	L2	L3		1	3	5		2	4	6		T1	T2	T3		I				0			
L1	L2	L3																													
1	3	5																													
2	4	6																													
T1	T2	T3																													
I																															
0																															
Rated uninterrupted current	$I_u$	A	800																												
Note on rated uninterrupted current $I_u$			Rated uninterrupted current $I_u$ is specified for max. cross-section.																												
Fuse cartridge		Size	NH3																												

## Technical data

### General

Standards			IEC/EN 60947, VDE 0660, IEC/EN 60204 Switch-disconnector according to IEC/EN 60947-3
Certifications			CE, RoHs
Ambient temperature			
Operation	θ	°C	-25 - +55
Storage	θ	°C	-30 - +80
Overvoltage category/pollution degree			III/3
Rated impulse withstand voltage	$U_{imp}$	kV	6
Rated insulation voltage	$U_i$	V	690
Mounting position			As required

### Contacts

Mechanical variables			
Number of poles			3 pole

Auxiliary contacts			
		N/O	0
		N/C	0
Electrical characteristics			
Rated operational voltage	$U_e$	V AC	690
Rated uninterrupted current	$I_u$	A	800
Note on rated uninterrupted current $I_u$			Rated uninterrupted current $I_u$ is specified for max. cross-section.
Heat dissipation per pole, current-dependent	$P_{vid}$	W	58

## Design verification as per IEC/EN 61439


Technical data for design verification			
Rated operational current for specified heat dissipation	$I_n$	A	800
Heat dissipation per pole, current-dependent	$P_{vid}$	W	58
Equipment heat dissipation, current-dependent	$P_{vid}$	W	0
Static heat dissipation, non-current-dependent	$P_{vs}$	W	0
Heat dissipation capacity	$P_{diss}$	W	0
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	55
IEC/EN 61439 design verification			
10.2 Strength of materials and parts			
10.2.2 Corrosion resistance			Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures			Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat			Meets the product standard's requirements.
10.2.3.3 Verification of resistance of insulating materials to abnormal heat and fire due to internal electric effects			Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation			Meets the product standard's requirements.
10.2.5 Lifting			Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact			Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions			Meets the product standard's requirements.
10.3 Degree of protection of ASSEMBLIES			Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances			Meets the product standard's requirements.
10.5 Protection against electric shock			Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components			Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections			Is the panel builder's responsibility.
10.8 Connections for external conductors			Is the panel builder's responsibility.
10.9 Insulation properties			
10.9.2 Power-frequency electric strength			Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage			Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material			Is the panel builder's responsibility.
10.10 Temperature rise			The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility			Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function			The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

## Technical data ETIM 7.0

Low-voltage industrial components (EG000017) / Fuse switch disconnecter (EC001040)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Off-load switch, circuit breaker, control switch / Fuse switch disconnecter (ecl@ss10.0.1-27-37-14-01 [AKF058013])			
Version as main switch			Yes
Version as safety switch			No
Max. rated operation voltage $U_e$ AC		V	690
Rated permanent current $I_u$		A	800
Rated operation power at AC-23, 400 V		kW	500

Conditioned rated short-circuit current Iq	kA	50
Rated short-time withstand current Icw	kA	0
Suitable for fuses		NH3
Number of poles		3
With error protection		No
Type of electrical connection of main circuit		Screw connection
Cable entry		Other
Equipped with connectors		Yes
Suitable for ground mounting		Yes
Suitable for front mounting 4-hole		No
Suitable for busbar mounting		No
Type of control element		Other
Position control element		Front side
Motor drive optional		No
Motor drive integrated		No
Version as emergency stop installation		No
Degree of protection (IP), front side		IP00

## Dimensions



## Assets (links)

### Declaration of CE Conformity

00003042

### Instruction Leaflets

IL008013ZU2018\_05

## Additional product information (links)

### IL008013ZU Safety switch-disconnector

IL008013ZU Safety switch-disconnector

[ftp://ftp.moeller.net/DOCUMENTATION/AWA\\_INSTRUCTIONS/IL008013ZU2018\\_05.pdf](ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/IL008013ZU2018_05.pdf)