

Soft starter, 41 A, 200 - 480 V AC, Us= 24 V AC/DC, Frame size FS3

Part no. **DS7-340SX041N0-N**
134916
 EL Number **4134201**
(Norway)

General specifications	
Product name	Eaton DS7 Soft starter
Part no.	DS7-340SX041N0-N
EAN	4015081317318
Product Length/Depth	139 millimetre
Product height	175 millimetre
Product width	93 millimetre
Product weight	1.8 kilogram
Compliances	Contact Manufacturer
Certifications	GB 14048.6 UL 508 CSA CSA Class No.: 321106 IEC/EN 60947-4-2 UL CSA File No.: 2511305 CSA22.2-14 CSA-C22.2 No 0-M91 UL File No.: E251034 CSA-C22.2 No 14-05 CE C-Tick UkrSEPRO
Product Tradename	DS7
Product Type	Soft starter
Product Sub Type	None
Catalog Notes	Ambient Operating Temperature up to 60 at 2% derating per Kelvin temperature rise External Reversing starter solution required Regulator supply: External supply voltage
Features & Functions	
Fitted with:	Internal bypass contacts Internal bypass
Functions	Soft start function Suppression of closing transients Suppression of DC components for motors Potential isolation between power and control sections Min. ramp time 1 s - fast switching (semiconductor contactor) Single direction
General information	
Class	Other
Connection to SmartWire-DT	No
Degree of protection	IP20 NEMA 1
Frame size	FS3
Mains voltage - min	200 V
Mains voltage - max	480 V
Overvoltage category	II
Pollution degree	2
Radio interference class	Class B (EN 55011)
Suitable for	Branch circuits, (UL/CSA)
Type	Soft starter for three-phase loads
Voltage type	AC/DC
Ambient conditions, mechanical	
Mounting position	Vertical
Shock resistance	8 g, 11 ms, Mechanical
Vibration resistance	2M2 to EN 60721-3-2

Climatic environmental conditions		
Altitude		Max. 2000 m Above 1000 m with 1 % derating per 100 m
Ambient operating temperature - min		-5 °C
Ambient operating temperature - max		40 °C
Ambient storage temperature - min		-25 °C
Ambient storage temperature - max		60 °C
Climatic proofing		Damp heat, cyclic, to IEC 60068-2-30 Damp heat, constant, to IEC 60068-2-3
Main conducting paths		
Overload cycle		AC-53a: 3 - 5: 75 - 10
Rated operational current (Ie) at AC-53		41 A
Rated operational voltage (Ue) - min		230 V
Rated operational voltage (Ue) - max		480 V
Short-circuit protection rating		3 x 170M3013, Type „2“ coordination (additional with the fuses for coordination type „1“), Main conducting paths NZMNI-M50/PKZM4-49, Type “1” coordination, Main conducting paths
Supply frequency		50/60 Hz, fLN, Main circuit
Voltage rating - max		480 V
Motor rating		
Assigned motor power at 200/208 V, 60 Hz, 3-phase		10 HP
Assigned motor power at 220/230 V, 60 Hz, 3-phase		15 HP
Assigned motor power at 460/480 V, 60 Hz, 3-phase		30 HP
Rated operational power at 220/230 V, 50 Hz		11 kW
Rated operational power at 400 V, 50 Hz		22 kW
Terminal capacities		
Terminal capacity (copper band)		9 x 9 x 0.8 mm, Main cables 2 x 9 x 0.8 mm, Main cables
Terminal capacity (flexible with ferrule)		1 x (0.5 - 1.5) mm ² , Control circuit cables 2 x (0.5 - 0.75) mm ² , Control circuit cables
Terminal capacity (solid)		2 x (6 - 25) mm ² , Main cables 1 x (0.5 - 2.5) mm ² , Control circuit cables 2 x (0.5 - 1.0) mm ² , Control circuit cables 1 x (25 - 70) mm ² , Main cables
Terminal capacity (solid/stranded AWG)		2 x (21 - 18), Control circuit cables 1 x (12 - 2/0), Main cables 1 x (21 - 14), Control circuit cables
Terminal capacity (stranded)		1 x (0.5 - 1.5) mm ² , Control circuit cables 2 x (6 - 25) mm ² , Main cables 2 x (0.5 - 1.0) mm ² , Control circuit cables 1 x (25 - 70) mm ² , Main cables
Screwdriver size		PZ2, 1 x 6 mm, Terminal screw, Standard screwdriver 0.6 x 3.5 mm, Terminal screws, Control circuit cables
Tightening torque		6 Nm (≤ 10 mm ²) 9 Nm (> 10 mm ²) 0.4 Nm, Screw terminals, Control circuit cables
Control circuit		
Current consumption		1.6 mA, Control circuit, Digital inputs, External 24 V 0,6 A/50 ms, Control circuit, Regulator supply at peak performance (close bypass) at 24 V DC 50 mA, Control circuit, Regulator supply
Drop-out time		350 ms, Control circuit, Digital Inputs, DC operated
Drop-out voltage		AC operated: 0 - 3 V, AC operated 0 - 3 V, DC operated
Pick-up time		250 ms at DC 250 ms at AC
Pick-up voltage		17.3 - 27 V DC 17.3 - 27 V AC
Rated control supply voltage (Us) at AC, 50 Hz - min		24 V
Rated control supply voltage (Us) at AC, 50 Hz - max		24 V
Rated control supply voltage (Us) at AC, 60 Hz - min		24 V
Rated control supply voltage (Us) at AC, 60 Hz - max		24 V
Rated control supply voltage (Us) at DC - min		24 V
Rated control supply voltage (Us) at DC - max		24 V

Input/Output	
Number of outputs	2 Relay Outputs (TOR, Ready)
Output voltage	250 V AC (relay outputs)
Protection	Finger and back-of-hand proof, Protection against direct contact
Rated control voltage (Uc)	24 V DC 24 V AC (-15 %/+10 %) 24 V DC (-15 %/+10 %) 24 V AC
Rated operational current (Ie) at AC-11	1 A
Soft start function	
Application	1-phase motors: No 3-phase motors: Yes Soft starting of three-phase asynchronous motors
Delay time	0 - 30 s, Soft start function, Ramp times
Ramp/run-up time	1 - 30 s
Start voltage	Max. 100 %, Soft start function, Start voltage = turn-off voltage Min. 30 %, Soft start function, Start voltage = turn-off voltage
Design verification	
Equipment heat dissipation, current-dependent Pvid	7 W
Heat dissipation capacity Pdis	0 W
Heat dissipation per pole, current-dependent Pvid	0 W
Rated operational current for specified heat dissipation (In)	41 A
Static heat dissipation, non-current-dependent Pvs	7 W
10.2.2 Corrosion resistance	Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures	Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat	Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects	Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation	Meets the product standard's requirements.
10.2.5 Lifting	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions	Meets the product standard's requirements.
10.3 Degree of protection of assemblies	Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances	Meets the product standard's requirements.
10.5 Protection against electric shock	Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components	Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections	Is the panel builder's responsibility.
10.8 Connections for external conductors	Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength	Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage	Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material	Is the panel builder's responsibility.
10.10 Temperature rise	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 Short-circuit rating	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Soft starter (EC000640)

Electric engineering, automation, process control engineering / Low-voltage switch technology / Load breakout, motor breakout / Semiconductor motor controller or soft starter (ecI@ss13-27-37-09-07 [AC0300016])

Rated operation current Ie at 40 °C Tu	A	41
Rated operating voltage Ue	V	230 - 480
Rated power three-phase motor, inline, at 230 V	kW	11
Rated power three-phase motor, inline, at 400 V	kW	22
Rated power three-phase motor, inside delta, at 230 V	kW	0
Rated power three-phase motor, inside delta, at 400 V	kW	0

Function			Single direction
Internal bypass			Yes
With display			No
Torque control			No
Rated surrounding temperature without derating		°C	40
Rated control supply voltage AC 50 Hz		V	24 - 24
Rated control supply voltage AC 60 Hz		V	24 - 24
Rated control supply voltage DC		V	24 - 24
Voltage type for actuating			AC/DC
Integrated motor overload protection			No
Release class			Other
Degree of protection (IP)			IP20
Degree of protection (NEMA)			1