



Proximity switch, E57 Premium+ Series, 1 NC, 2-wire, 20 - 250 V AC, M18 x 1 mm, S<sub>n</sub>= 8 mm, Non-flush, Stainless steel, 2 m connection cable



Powering Business Worldwide™

**Part no.** E57LBL18A2E  
**Catalog No.** 136043  
**Alternate Catalog No.** E57LBL18A2E

## Delivery program

|                           |                |    |                      |
|---------------------------|----------------|----|----------------------|
| Basic function            |                |    | Inductive Sensors    |
| Product range             |                |    | E57 Premium+ Series  |
| Connection                |                |    | 2-wire               |
| Design (outer dimensions) |                | mm | M18 x 1              |
| Rated operational voltage | U <sub>e</sub> |    | 20 - 250 V AC        |
| Rated switching distance  | S <sub>n</sub> | mm | 8                    |
| Type of mounting          |                |    | Non-flush            |
| For connection of:        |                |    | 2 m connection cable |
| <b>Contacts</b>           |                |    |                      |
| N/C = Normally closed     |                |    | 1 NC                 |
| Material                  |                |    | Stainless steel      |
| Degree of Protection      |                |    | IP67                 |

## Technical data

### General

|                             |  |   |                            |
|-----------------------------|--|---|----------------------------|
| Standards                   |  |   | IEC/EN 60947-5-2           |
| Ambient temperature         |  |   | -25 - +70                  |
| Mechanical shock resistance |  | g | 30<br>Shock duration 11 ms |
| Degree of Protection        |  |   | IP67                       |

### Characteristics

|  |                |     |                             |
|--|----------------|-----|-----------------------------|
| Rated switching distance   |                |     |                             |
| Rated switching distance   | S <sub>n</sub> | mm  | 8                           |
| Repetition accuracy of S <sub>n</sub>  |                | %   | 3                           |
| Temperature drift of S <sub>n</sub>  |                | %   | 10                          |
| Switching hysteresis of S <sub>n</sub>   |                | %   | 20                          |
| Rated operational voltage  | U <sub>e</sub> |     | 20 - 250 V AC               |
| Operating current in the switched state at 24 V DC                             | I <sub>b</sub> | mA  | 10                          |
| Maximum load current   | I <sub>e</sub> | mA  | < 500 (25 °C) / 250 (70 °C) |
| Voltage drop at I <sub>e</sub>   | U <sub>d</sub> | V   | 2.5                         |
| Switching Frequency  |                | Hz  | 20                          |
| Min. load current  | I <sub>e</sub> | mA  | 1                           |
| Residual current through the load in the blocked state at 230 V AC and 24 V DC | I <sub>r</sub> | mA  | 0.1                         |
| Switching state display  |                | LED | Red                         |
| Connection   |                |     | 2-wire                      |
| Contacts   |                |     |                             |
| N/C = Normally closed  |                |     | 1 NC                        |
| Style  |                |     |                             |
| Design (outer dimensions)  |                | mm  | M18 x 1                     |
| For connection of:   |                |     | 2 m connection cable        |
| Material   |                |     | Stainless steel             |

## Design verification as per IEC/EN 61439

|  |  |    |     |
|--|--|----|-----|
| Technical data for design verification |  |    |     |
| Operating ambient temperature min.     |  | °C | -25 |

Operating ambient temperature max.

°C

70

## Technical data ETIM 7.0

Sensors (EG000026) / Inductive proximity switch (EC002714)

Electric engineering, automation, process control engineering / Binary sensor technology, safety-related sensor technology / Proximity switch / Inductive proximity switch (ecl@ss10.0.1-27-27-01-01 [AGZ376015])

|  |    |                        |
|--|----|------------------------|
| Width sensor   | mm | 0                      |
| Height of sensor   | mm | 0                      |
| Length of sensor   | mm | 66                     |
| Diameter sensor  | mm | 18                     |
| Mechanical mounting condition for sensor                     |    | Not flat               |
| Switching distance   | mm | 8                      |
| Suitable for safety functions                                |    | No                     |
| Type of switch function                                      |    | Breaker contact        |
| Type of switching output                                     |    | Two-wire               |
| Type of electric connection                                  |    | Cable                  |
| Number of semiconductor outputs with signalling function     |    | 1                      |
| Number of contact energized outputs with signalling function |    | 0                      |
| Number of protected semiconductor outputs                    |    | 0                      |
| Number of protected contact energized outputs                |    | 0                      |
| Type of actuation  |    | Metallic Target        |
| Type of interface  |    | None                   |
| Type of interface for safety communication                   |    | None                   |
| Construction type housing                                    |    | Cylinder, screw-thread |
| Coating housing  |    | Other                  |
| Cascadable   |    | No                     |
| Category according to EN 954-1                               |    | B                      |
| SIL according to IEC 61508                                   |    | None                   |
| Performance level acc. EN ISO 13849-1                        |    | None                   |
| Max. output current at protected output                      | mA | 0                      |
| Supply voltage   | V  | 20 - 250               |
| Rated control supply voltage Us at AC 50HZ                   | V  | 20 - 250               |
| Rated control supply voltage Us at AC 60HZ                   | V  | 20 - 250               |
| Rated control supply voltage Us at DC                        | V  | 0 - 0                  |
| Voltage type   |    | AC                     |
| Switching frequency  | Hz | 20                     |
| With monitoring function downstream switching devices        |    | No                     |
| Material housing   |    | Metal                  |
| Compression-resistant  |    | No                     |
| Explosion safety category for gas                            |    | None                   |
| Explosion safety category for dust                           |    | None                   |
| Interference resistance to magnetic fields                   |    |                        |

## Approvals

|                             |  |   |
|-----------------------------|--|---|
| Product Standards           |  | UL 508; CSA-C22.2 No. 14; IEC60947-5-2; CE marking  |
| UL File No.                 |  | E166051   |
| UL Category Control No.     |  | NRKH, NRKH7   |
| CSA File No.                |  | 50513   |
| CSA Class No.               |  | 3211-03   |
| North America Certification |  | UL listed, CSA certified                            |
| Max. Voltage Rating         |  | 250 V AC  |
| Degree of Protection        |  | IEC: IP67, IP69K; UL/CSA Type: 4, 4x, 6, 6P, 12, 13 |

## Dimensions

① Sensor surface

## Assets (links)

### Declaration of CE Conformity

00003158

### Instruction Leaflets

IL05301003Z2018\_05

## Additional product information (links)

### IL05301003Z Premium Plus Series Inductive Sensors +Short, +Miniature

|  |   |
|--|---|
| IL05301003Z Premium Plus Series Inductive Sensors +Short, +Miniature | <a href="ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/IL05301003Z2018_05.pdf">ftp://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/IL05301003Z2018_05.pdf</a> |
|--|---|