




Connection cable, 3p, AC, coupling m12 angled, open end, L=10m

Part no. CSAR3F3CY2210
Catalog No. 136264
Alternate Catalog No. CSAR3F3CY2210

Delivery program

| | | | |
|---------------------|--|----|---|
| Basic function | | | Accessories |
| Accessories | | | Connecting cables |
| Length | | mm | 10000 |
| Pin assignment | | |  <p>1 = Green 2 = Red/Black 3 = Red/White</p> |
| Voltage type | | | AC |
| Number of poles | | | 3 pole |
| Style output side | | | Cable end, open |
| Style input side | | | Coupling, angled |
| For use with | | | |
| For use with | | | AC sensors, 3 pole, M12 |

Design verification as per IEC/EN 61439

| | | | |
|--|--|----|-----|
| Technical data for design verification | | | |
| Operating ambient temperature min. | | °C | -25 |
| Operating ambient temperature max. | | °C | 70 |

Technical data ETIM 7.0

| | | | |
|---|--|------|--------------|
| Sensors (EG000026) / Sensor-actuator patch cord (EC001855) | | | |
| Electric engineering, automation, process control engineering / Cable, wire / Ready-made data cable / Assembled sensor actuator-line (ecl@ss10.0.1-27-06-03-11 [AFR601003]) | | | |
| Number of poles | | | 3 |
| Type of electrical connection, field-sided | | | M12 |
| Type of plug-in contact, field sided | | | Female (bus) |
| Positioning cable feed, field-sided | | | Angled |
| Type of electrical connection, box-sided | | | Other |
| Type of plug-in contact, box-sided | | | |
| Positioning cable feed, box-sided | | | Other |
| Cable length | | m | 10 |
| Material of cable sheath | | | Other |
| Halogen free | | | No |
| Colour cable sheath | | | Other |
| With LED indication | | | No |
| Screened | | | No |
| Type of cable | | | Multi-core |
| Vulcanize | | | No |
| Material contact body | | | Other |
| Material of contact surface | | | Other |
| Permitted cable outer temperature after assembling without vibration | | °C | 40 - 70 |
| Permitted cable outer temperature during assembling/handling | | °C | 40 - 70 |
| Rated current In | | A | 0 |
| Rated voltage | | V | 0 |
| Continuity resistor | | mOhm | 0 |
| Degree of protection (IP) | | | Other |

Approvals

Product Standards

CE marking