

Conductor connection terminal M8 for 10mm



Part no. **AKU-M8/10**
138362

General specifications		
Product name		Eaton xEffect SASY 60i busbar terminal
Part no.		AKU-M8/10
EAN		4015081351428
Product Length/Depth		36 millimetre
Product height		32 millimetre
Product width		30 millimetre
Product weight		0.165 kilogram
Compliances		RoHS conform
Product Tradename		xEffect SASY 60i
Product Type		Busbar system component
Product Sub Type		Busbar terminal
Delivery program		
Type		Compact system Connection 185 mm system 60 mm system
Technical Data - Electrical		
Rated operation current (Ie)		490 A
Rated operational current		490 A
Rated operational current (Ie) - max		490 A
Technical Data - Mechanical		
Busbar thickness - min		10 mm
Busbar thickness - max		10 mm
Busbar width - min		0 mm
Busbar width - max		0 mm
Terminal contact area		8 mm with M8 bolt
Terminal capacity (conductor)		Cable lugs M8
Conductor cross section - max		0 mm ²
Width clamp		30 mm
Additional information		
Functions		Connections Universal conductor connection terminal
Special features		With integrated retaining spring, open terminal chamber and captive terminal screw
Suitable for		Flat rail Round conductor connection
Used with		Double T profile All 10 mm thick flat busbars Compact system 60 mm system Connection 185 mm system

Technical data ETIM 9.0

Low-voltage industrial components (EG000017) / Busbar terminal (EC000001)		
Electric engineering, automation, process control engineering / Terminal block systems and system components / Terminal block systems / Busbar terminal (ecl@ss13-27-25-01-16 [BAA025018])		
Busbar thickness	mm	10 - 10
Busbar width	mm	0 - 0
Suitable for		Flat rail
Width clamp	mm	30
Max. conductor cross section	mm ²	0
Max. rated operation current Ie	A	490

Suitable for round conductor connection			Yes
Suitable for sector conductor connection			No
Suitable for strip conductor connection			No