



Oil fuse-link, medium voltage, 16 A, AC 15.5 kV, BS2692 F01, 63.5 x 254 mm, back-up, BS, IEC, ESI, with striker

Catalog No. 15.50EFMA16

Similar to illustration

Delivery program

Product range			Fuse
Basic function			Oil fuse-link
Field of application			medium voltage
Rated current	I	A	16
Rated voltage			AC 15.5 kV
Construction size			BS2692 F01
Size			63.5 x 254 mm
Utilization category			back-up
Status indicator			with striker
Description			oil-tight
Breaking Capacity		kA	40
usable for size/applications			protection of primary side transformer, and oil-filled fuse switch combination unit
Standard/Approval			BS IEC ESI
Shape			cylindrical
Standards/Regulations			BS2692-1 IEC 60282-1 ESI 12-8

Technical data ETIM 7.0

Circuit breakers and fuses (EG000020) / Medium-/high voltage fuse (EC003507)			
Rated current		A	16
Rated voltage		kV	15.5
Voltage type			AC
Rated frequency		Hz	50 - 50
Breaking capacity		kA	40
Utilization category			Other
Application			Primary side transformer protection
Length		mm	254
Diameter		mm	63.5
Performance category according to IEC 60282-1			Back-up
With striker			Yes
Standard			British Standard
Release characteristic			Other
Installation technique			Oil